

TECH SHEET

RUBBER COMPOUND

Procedure Warning: (For industrial use by professionally trained personnel only) If being injected, steps should be taken to insure that the injection pressure in conjunction with pressure that may occur from gassing off of the compound does not exceed the pressure limitations of the piping system. If the compound is gassing off, gasses should be vented. Also, be aware it is quite common that the application temperature will exceed the compound flash point. Be aware of the possibility of a flash and take necessary precautions. See section 8 of SDS for personal protective equipment. Refer to product SDS and technical data for reactivity and compatibility information.

Description: One component high temperature liquid rubber sealant compound. Red color

Temperature Range: -85°F. (-65°C.) to 600°F. (315°C.) **Application:** Flanges and enclosures (water service)

Curing: Cures to a low durometer solid. DO NOT expose unused material to air or moisture. A partial cure occurs in approx. 5 minutes. Full cure will take up to 24 hours. **Shelf Life:** 6 months in unopened container

Packaged: 10.3 oz (.3 L.) tubes (12 per

case), Gallons (3.7 L.) and 4.5 Gallon (17 L.) Pails

Federal Specification: Meets or exceeds the following specifications: USDA for use in federally inspected Meat and poultry plants. FDA Regulation No.21 CFR 177.2600, TT-S-00230C (COM-NBS) Class A, and TT-S-001543A (COM-NBS) Class A, Canadian 19-GP-9MA Type 1 and MIL-A-46106B Amend. 3, Type 1.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE.

NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS

Disclaimer: The information & recommendations of Jet-Lube LLC / Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Jet-Lube LLC / Deacon, the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Jet-Lube LLC / Deacon recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.