



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 10-11-2012

Revision Date 03-01-2018

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

Section 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product Name MOLY MIST (Bulk)TM

Product Code(s) 160

Other means of identification

Extended Description Ketones, liquid, n.o.s.

UN Number UN1993

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of manufacturer or importer

Supplier Identification XTEX

Address
XTEX Ltd
ABN 40 121 722 236
7 Arnold Street
Cheltenham, VIC 3192

Telephone TEL: 1300-00-XTEX(9839)

E-mail sales@xtex.com.au

For further information, please contact

Responsible Persons Product Safety Department

Emergency telephone number

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL) Information Center, Australia: 13 11 26
Information Center, New Zealand: 0800 764 766



Section 2: Hazard(s) identification

GHS Classification

Flammable Liquids	Category 2
Acute toxicity - Inhalation (Gases)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2A - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elements

Flame

Exclamation mark



Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H332 - Harmful if inhaled
 H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Keep cool

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 If skin irritation occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician if you feel unwell
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up

Precautionary Statements - Disposal



Dispose of contents/container to an approved waste disposal plant

Other hazards

May be harmful if swallowed
 May be harmful in contact with skin
 Harmful to aquatic life with long lasting effects
 Harmful to aquatic life

General Hazards No information available.

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable.

Mixture

Chemical name	CAS-No	Percent
Acetone	67-64-1	>60
Methyl ethyl ketone	78-93-3	10-<30
Xylenes (o-, m-, p- isomers)	1330-20-7	10-<30
Molybdenum (IV) sulfide	1317-33-5	<10
Isopropyl alcohol	67-63-0	<10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

First aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Emergency telephone number	Poisons Information Center, Australia: 13 11 26 Poisons Information Center, New Zealand: 0800 764 766
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty

in breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous Combustion Products Carbon oxides

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3YE.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.

Other Information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep out of the reach of children.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Section 8: Exposure controls and personal protection**Control parameters****Exposure Limits**

Chemical name	Australia
Acetone - 67-64-1	1185 mg/m ³ 500 ppm
Methyl ethyl ketone - 78-93-3	150 ppm 445 mg/m ³ 300 ppm STEL 890 mg/m ³ STEL
Xylenes (o-, m-, p- isomers) - 1330-20-7	80 ppm 350 mg/m ³ 150 ppm STEL 655 mg/m ³ STEL
Molybdenum (IV) sulfide - 1317-33-5	TWA: 10 mg/m ³
Isopropyl alcohol - 67-63-0	TWA: 400 ppm TWA: 983 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³

Legend

See section 16 for terms and abbreviations.

Chemical name	Australia	ACGIH - American Conference of Governmental Industrial Hygienists
Acetone - 67-64-1	-	25 mg/L
Methyl ethyl ketone - 78-93-3	-	2 mg/L
Xylenes (o-, m-, p- isomers) - 1330-20-7	-	1.5 g/g creatinine
Isopropyl alcohol - 67-63-0	-	40 mg/L

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves. Protective gloves. Rubber gloves. Nitrile rubber. Neoprene gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties**Physical and Chemical Properties**

Physical state Liquid
Appearance Black
Odor Ether
Color No information available
Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	7	
Melting / freezing point	-95 °C	None known
Boiling point / boiling range	-18--162 °C	None known
Flash Point	> -20 °C	
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.85	
Water Solubility	Partially soluble	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	Not Applicable	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other Information

Softening Point	No information available
Molecular Weight	No information available
VOC Content (%) 314	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes.

Possibility of Hazardous Reactions

Possibility of hazardous reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products

Hazardous Decomposition Products Carbon oxides.

Section 11: Toxicological information

Acute Toxicity**Information on likely routes of exposure****Product Information**

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). Irritating to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms

Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	3,721.00 mg/kg
ATEmix (dermal)	2,440.00 mg/kg
ATEmix (inhalation-gas)	4,500.00 ppm
ATEmix (inhalation-vapor)	21.00 mg/L
ATEmix (inhalation-dust/mist)	7.09 mg/L

Unknown acute toxicity

88.9 % of the mixture consists of ingredient(s) of unknown toxicity

19.6 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

62 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

88.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

64.2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

44.3 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Methyl ethyl ketone	= 2737 mg/kg (Rat)	= 6480 mg/kg (Rabbit)	23500 mg/m ³
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Molybdenum (IV) sulfide	-	-	> 2820 mg/m ³ (Rat) 4 h
Isopropyl alcohol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h

Legend

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Irritating to skin.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Irritating to eyes.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Unknown aquatic toxicity 19.6 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone	-	96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L
Methyl ethyl ketone	-	LC50 96 h: 3130-3320 mg/L flow-through (Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h: 4025 - 6440 mg/L Static (Daphnia magna) EC50 48 h: = 5091 mg/L (Daphnia magna) EC50 48 h: > 520 mg/L (Daphnia magna)
Xylenes (o-, m-, p-isomers)	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)	EC50 = 0.0084 mg/L 24 h	EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)
Isopropyl alcohol	96h EC50: > 1000 mg/L (Desmodesmus subspicatus) 72h EC50: > 1000 mg/L (Desmodesmus subspicatus)	96h LC50: > 1400000 µg/L (Lepomis macrochirus) 96h LC50: = 11130 mg/L (Pimephales promelas) 96h LC50: = 9640 mg/L (Pimephales promelas)	-	48h EC50: = 13299 mg/L

Persistence and degradability

Persistence and Degradability No information available.

Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Log Pow
Acetone	-0.24
Methyl ethyl ketone	0.29
Xylenes (o-, m-, p- isomers)	2.77 - 3.15
Isopropyl alcohol	0.05

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Section 14: Transport information

ADG

UN Number UN1993
Proper shipping name KETONES, LIQUID, N.O.S.
Hazard Class 3
Packing group II

Hazchem code •3YE

IATA

UN-No. UN1993
Proper Shipping Name Flammable liquid, n.o.s.
Hazard Class 3
Packing Group II
ERG Code 3L
Description UN1993, Flammable liquid, n.o.s. (Acetone, Methyl ethyl ketone), 3, II

IMDG/IMO

UN-No. UN1993
Proper Shipping Name Flammable liquid, n.o.s.
Hazard Class 3
Packing Group II
EmS-No. F-E, S-E
Description UN1993, Flammable liquid, n.o.s. (Acetone, Methyl ethyl ketone), 3, II, (-20°C c.c.)

Transport in bulk according to Annex II of MARPOL and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

The below table provides the relevant information for classification of this product according to the regulation. This information should be used to appropriately determine if a classification is relevant to the overall product

Chemical name	Percent	Poison Schedule Number	Standard for the Uniform Scheduling of Drugs and Poisons(SUSDP)
Acetone 67-64-1	>60	5	5: except in preparations containing <=25% of designated solvents
Methyl ethyl ketone 78-93-3	10-<30	5	Schedule 5 (except in preparations containing <=25% of designated solvents)
Xylenes (o-, m-, p- isomers) 1330-20-7	10-<30	6	Schedule 6 (except its derivatives;except in preparations containing <=50% of Xylene or Xylene and Toluene)

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III
Liquids with flash points <61°C kept above their boiling points at ambient conditions

Threshold quantity (T)

50 000
200

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Acetone - 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Methyl ethyl ketone - 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Xylenes (o-, m-, p- isomers) - 1330-20-7	10 tonne/yr Threshold category 1 including individual or mixed isomers 20 MW Threshold category 2b total

	60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Isopropyl alcohol - 67-63-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

TSCA	Complies.
DSL/NDSL	Complies.
EINECS/ELINCS	Complies.
ENCS	Not determined.
KECL	Not determined.
PICCS	Not determined.
AICS	Complies.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

Section 16: Any other relevant information

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	10-11-2012
Revision Date	03-01-2018
Revision Note	Initial Release

Key or legend to abbreviations and acronyms used in the safety data sheet**Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	-	Skin designation



C Carcinogen

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet