



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 07-25-2012

Revision Date 03-01-2018

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

Section 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product Name MOLY-MIST™ AEROSOL

Product Code(s) 160

Other means of identification

Extended Description Aerosols

UN Number UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of manufacturer or importer

Supplier Identification XTEX

Address
XTEX Ltd
ABN 40 121 722 236
7 Arnold Street
Cheltenham, VIC 3192

Telephone TEL: 1300-00-XTEX(9839)

E-mail sales@xtex.com.au

For further information, please contact

Responsible Persons Product Safety Department

Emergency telephone number

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL) Information Center, Australia: 13 11 26
Information Center, New Zealand: 0800 764 766



Section 2: Hazard(s) identification

GHS Classification

Aerosols	Category 1
Acute toxicity - Inhalation (Gases)	Category 4 - (H332)
Acute toxicity - Inhalation (Vapors)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2A - (H319)
Skin sensitization	Category 1 - (H317)
Germ cell mutagenicity	Category 1B - (H340)
Carcinogenicity	Category 1A - (H350)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elements

Flame

Exclamation mark

Health hazard



Signal word

Danger

Hazard statements

H222 - Extremely flammable aerosol

H229 - Pressurized container: May burst if heated

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

H340 - May cause genetic defects

H350 - May cause cancer

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

May be harmful if swallowed

May be harmful in contact with skin

Harmful to aquatic life with long lasting effects

Harmful to aquatic life

General Hazards

No information available.

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable.

Mixture

Chemical name	CAS-No	Percent
Acetone	67-64-1	30-<60
Petroleum distillates	68476-85-7	10-<30
Methyl ethyl ketone	78-93-3	10-<30
Xylenes (o-, m-, p- isomers)	1330-20-7	10-<30
Bisphenol A - Epichlorohydrin polymer	25068-38-6	<10
Molybdenum (IV) sulfide	1317-33-5	<10
Mineral Spirits	64741-41-9	<10

Section 4: First aid measures

First aid measures

General advice

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

Emergency telephone number

Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Inhalation

Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact

May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.



Never give anything by mouth to an unconscious person. Get medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing vapors or mists.

Other Information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.



Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
--	--

Section 7: Handling and storage, including how the chemical may be safely used**Precautions for safe handling**

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.
--------------------------------	---

General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.
---------------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.
---------------------------	--

Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
-------------------------------	--

Section 8: Exposure controls and personal protection**Control parameters****Exposure Limits**

Chemical name	Australia
Acetone - 67-64-1	500 ppm 1185 mg/m ³ 1000 ppm STEL 2375 mg/m ³ STEL
Petroleum distillates - 68476-85-7	1000 ppm 1800 mg/m ³
Methyl ethyl ketone - 78-93-3	150 ppm

	445 mg/m ³ 300 ppm STEL 890 mg/m ³ STEL
Xylenes (o-, m-, p- isomers) - 1330-20-7	80 ppm 350 mg/m ³ 150 ppm STEL 655 mg/m ³ STEL
Molybdenum (IV) sulfide - 1317-33-5	TWA: 10 mg/m ³

Legend See section 16 for terms and abbreviations.

Chemical name	Australia	ACGIH - American Conference of Governmental Industrial Hygienists
Acetone - 67-64-1	-	25 mg/L
Methyl ethyl ketone - 78-93-3	-	2 mg/L
Xylenes (o-, m-, p- isomers) - 1330-20-7	-	1.5 g/g creatinine

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Impervious gloves. Wear suitable gloves. Nitrile rubber. Neoprene gloves. Rubber gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Physical and Chemical Properties

Physical state Aerosol
Appearance Black
Odor Ether
Color No information available
Odor Threshold No data available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	7	
Melting / freezing point	-95.35 °C	None known
Boiling point / boiling range	-18 - 162 °C	None known
Flash Point	> -20 °C	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.85	



Water Solubility	Soluble in water	
Solubility(ies)	Completely soluble	None known
Partition coefficient: n-octanol/water	-0.2	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
<u>Other Information</u>		
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes.

Possibility of Hazardous Reactions

Possibility of hazardous reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products

Hazardous Decomposition Products Carbon oxides.

Section 11: Toxicological information

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of

	respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). Irritating to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. May cause sensitization by skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	4,206.00 mg/kg
ATEmix (dermal)	2,162.00 mg/kg
ATEmix (inhalation-gas)	4,500.00 ppm
ATEmix (inhalation-vapor)	19.00 mg/L
ATEmix (inhalation-dust/mist)	6.00 mg/L

Unknown acute toxicity	90 % of the mixture consists of ingredient(s) of unknown toxicity
	33.1 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
	73 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
	90 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
	73 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
	58.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Methyl ethyl ketone	= 2737 mg/kg (Rat)	= 6480 mg/kg (Rabbit)	23500 mg/m ³
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Bisphenol A - Epichlorohydrin polymer	11400 mg/kg (Rat)	-	-
Molybdenum (IV) sulfide	-	-	> 2820 mg/m ³ (Rat) 4 h

Legend

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Irritating to skin.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Irritating to eyes.
Respiratory or skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	Classification based on data available for ingredients. Contains a known or suspected mutagen.
Carcinogenicity	Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia
Petroleum distillates	Carc. 1B
Mineral Spirits	Carc. 1B

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Unknown aquatic toxicity 7 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone	-	LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Methyl ethyl ketone	-	LC50 96 h: 3130-3320 mg/L flow-through (Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h: 4025 - 6440 mg/L Static (Daphnia magna) EC50 48 h: = 5091 mg/L (Daphnia magna) EC50 48 h: > 520 mg/L (Daphnia magna)
Xylenes (o-, m-, p-isomers)	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio)	EC50 = 0.0084 mg/L 24 h	EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)

		LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)		
Mineral Spirits	72h EC50: = 4700 mg/L (Pseudokirchneriella subcapitata)	-	-	-

Persistence and degradability

Persistence and Degradability No information available.

Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Log Pow
Acetone	-0.24
Petroleum distillates	2.8
Methyl ethyl ketone	0.29
Xylenes (o-, m-, p- isomers)	2.77 - 3.15

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Endocrine Disruptor Information

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Bisphenol A - Epichlorohydrin polymer	Group III Chemical	-	-

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

ADG

UN Number	UN1950
Proper shipping name	AEROSOLS
Hazard Class	2.1

IATA

UN-No. UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
Packing Group None
ERG Code 10L
Description UN1950,Aerosols, flammable,2.1

IMDG/IMO

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group None
EmS-No. F-D, S-U
Description UN1950, Aerosols,2.1,FP -20C

Transport in bulk according to Annex II of MARPOL and the IBC Code
 No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

The below table provides the relevant information for classification of this product according to the regulation. This information should be used to appropriately determine if a classification is relevant to the overall product

Chemical name	Percent	Poison Schedule Number	Standard for the Uniform Scheduling of Drugs and Poisons(SUSDP)
Acetone 67-64-1	30-<60	5	Schedule 5 (except in preparations containing <=25% of designated solvents)
Methyl ethyl ketone 78-93-3	10-<30	5	Schedule 5 (except in preparations containing <=25% of designated solvents)
Xylenes (o-, m-, p- isomers) 1330-20-7	10-<30	6	Schedule 6 (except its derivatives;except in preparations containing <=50% of Xylene or Xylene and Toluene)

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Named hazardous chemicals

Chemical name	Threshold quantity (T)
Petroleum distillates - 68476-85-7	200 tonne TQ

Hazardous chemical
Compressed or liquefied gases of Division 2.1 or Subsidiary Risk 2.1

Threshold quantity (T)
200

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Acetone - 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Methyl ethyl ketone - 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Xylenes (o-, m-, p- isomers) - 1330-20-7	10 tonne/yr Threshold category 1 including individual or mixed isomers 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

TSCA	Complies.
DSL/NDL	Complies.
EINECS/ELINCS	Complies.
ENCS	Not determined.
KECL	Not determined.
PICCS	Not determined.
AICS	Complies.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

Section 16: Any other relevant information

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 07-25-2012

Revision Date 03-01-2018

Revision Note Initial Release

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	-	Skin designation
C	Carcinogen		

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet