

SECTION 1: Identification of Product and Company

1.1. Product identifier

Trade name : RUN-N-SEAL® EXTREME
Product code : 12215

1.2. Company identification

Manufacturer

Whitmore Manufacturing LLC
930 Whitmore Drive 75087 Rockwall, Texas USA
T 1.972.771.1000
Regulatory@whitmores.com - www.jetlube.com

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week
Within USA and Canada: 1.800.424.9300
Outside USA and Canada: +1.703.527.3887
(collect calls accepted)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725)

Hazardous to the aquatic environment – Acute Hazard, Category 2
Hazardous to the aquatic environment – Chronic Hazard, Category 2

2.2. Label elements

GHS BR labelling

Hazard pictograms (GHS BR)



Hazard statements (GHS BR) : H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (GHS BR) : P273 - Avoid release to the environment.
P391 - Collect spillage.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
graphite	CAS-No.: 7782-42-5	19.452105 – 20.3939964
talc	CAS-No.: 14807-96-6	5 – 10
Benzenesulfonic acid, C10-16-alkyl derivs. Calcium salt	CAS-No.: 68584-23-6	2 – 5

RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

Name	Product identifier	%
white mineral oil (petroleum)	CAS-No.: 8042-47-5	2 – 5
Octadecanoic acid, 12-hydroxy-, calcium salt (2:1)	CAS-No.: 3159-62-4	2 – 5
Carbamodithioicacid,dibutyl-,methylenester	CAS-No.: 10254-57-6	2 – 5
chalk	CAS-No.: 1317-65-3	≥ 1.48813035

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Keep only in original container. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Keep cool. Protect from sunlight.
Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:					
Neoprene or nitrile rubber gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	2 (> 30 minutes)	0.3 mm - 0.6 mm		

Eye protection:

Wear eye protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

No respiratory protection needed under normal use conditions

RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: Black
Odour	: Petroleum-like odour
Odour threshold	: Not available
pH	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: > 232 °C Open cup
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20 °C	: Not available
Relative density	: Not available
Density	: 1.25 g/m ³
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: > 25 cSt
Viscosity, dynamic	: Not available

9.2. Other information

Not available

SECTION 10: Stability and reactivity

Chemical stability	: Stable under normal conditions of use.
Conditions to avoid	: Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hazardous decomposition products	: No hazardous decomposition products known at room temperature.
Incompatible materials	: Consult supplier(s) of these materials for specific recommendations.
Possibility of hazardous reactions	: None under normal use.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not available
Acute toxicity (dermal)	: Not available
Acute toxicity (inhalation)	: Not available

graphite (7782-42-5)	
LD50 oral rat	> 2000 mg/kg (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LC50 Inhalation - Rat	> 2000 mg/m ³ air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust))
LC50 Inhalation - Rat (Dust/Mist)	> 2 mg/l Source: ECHA
talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))
LC50 Inhalation - Rat (Dust/Mist)	> 2.1 mg/l Source: ECHA

RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

talco (14807-96-6)	
ATE BR (dermal)	2500 mg/kg bodyweight
Carbamodithioicacid,dibutyl-,methyleeneester (10254-57-6)	
LD50 oral rat	> 16000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:Section 1500.40-Federal Hazardous Substances Act Regulations-16 CFR-P. 123, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE BR (dermal)	2500 mg/kg bodyweight
Octadecanoic acid, 12-hydroxy-, calcium salt (2:1) (3159-62-4)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
ATE BR (oral)	2500 mg/kg bodyweight
ATE BR (dermal)	2500 mg/kg bodyweight
white mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal)
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol))
ATE BR (dermal)	2500 mg/kg bodyweight
Benzenesulfonic acid, C10-16-alkyl derivs. Calcium salt (68584-23-6)	
LD50 oral rat	> 16000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:Section 772.112-21 CFR 40
LD50 dermal rabbit	> 4000 mg/kg bodyweight Animal: rabbit, Guideline: other:40 CFR, Section 163.81-2, Federal Register, August 22, 1978
LC50 Inhalation - Rat	> 1.9 mg/l air Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)
ATE BR (dermal)	2500 mg/kg bodyweight
chalk (1317-65-3)	
LD50 oral rat	6450 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg
ATE BR (oral)	6450 mg/kg bodyweight
ATE BR (dermal)	2500 mg/kg bodyweight
Skin corrosion/irritation	: Not available
graphite (7782-42-5)	
pH	7 (1.3 %)
talco (14807-96-6)	
pH	9
chalk (1317-65-3)	
pH	8.5 – 9
Serious eye damage/irritation	: Not available
graphite (7782-42-5)	
pH	7 (1.3 %)

RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

talc (14807-96-6)	
pH	9
chalk (1317-65-3)	
pH	8.5 – 9
Respiratory or skin sensitisation	: Not available
Germ cell mutagenicity	: Not available
Carcinogenicity	: Not available
talc (14807-96-6)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not available
STOT-single exposure	: Not available
STOT-repeated exposure	: Not available
graphite (7782-42-5)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.000279 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Carbamodithioicacid,dibutyl-,methylenester (10254-57-6)	
LOAEL (oral, rat, 90 days)	314 – 425.2 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Benzenesulfonic acid, C10-16-alkyl derivs. Calcium salt (68584-23-6)	
NOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Aspiration hazard	: Not available
RUN-N-SEAL® EXTREME	
Viscosity, kinematic	> 25 mm²/s
graphite (7782-42-5)	
Animal studies and expert judgment for classification	False
talc (14807-96-6)	
Animal studies and expert judgment for classification	False
Carbamodithioicacid,dibutyl-,methylenester (10254-57-6)	
Animal studies and expert judgment for classification	False
Viscosity, kinematic	1383 mm²/s Temp.: 'other:25.0°C' Parameter: 'kinematic viscosity (in mm²/s)'
Octadecanoic acid, 12-hydroxy-, calcium salt (2:1) (3159-62-4)	
Animal studies and expert judgment for classification	False
white mineral oil (petroleum) (8042-47-5)	
Animal studies and expert judgment for classification	False
Viscosity, kinematic	> 3 mm²/s (40 °C, ISO 3104: Determination of kinematic viscosity and calculation of dynamic viscosity)
Benzenesulfonic acid, C10-16-alkyl derivs. Calcium salt (68584-23-6)	
Animal studies and expert judgment for classification	False
Viscosity, kinematic	77.4 mm²/s Temp.: 'other:100.0°C' Parameter: 'cStCentistokes'
chalk (1317-65-3)	
Animal studies and expert judgment for classification	False

RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

graphite (7782-42-5)

LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
EC50 72h - Algae [1]	19 mg/l
EC50 72h - Algae [2]	7.2 mg/l
ErC50 algae	> 100 mg/l
NOEC (chronic)	47 mg/l

talca (14807-96-6)

LC50 - Fish [1]	89581 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)
EC50 96h - Algae [1]	7203 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

Carbamodithioic acid, dibutyl-, methylene ester (10254-57-6)

LC50 - Fish [1]	> 0.06 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 0.052 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.0325 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

white mineral oil (petroleum) (8042-47-5)

LC50 - Fish [1]	> 100 mg/l
-----------------	------------

Benzenesulfonic acid, C10-16-alkyl derivs. Calcium salt (68584-23-6)

EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

chalk (1317-65-3)

LC50 - Fish [1]	> 10000 mg/l (96 h, Oncorhynchus mykiss, Literature)
EC50 - Crustacea [1]	> 1000 mg/l (48 h, Daphnia magna, Literature)
EC50 72h - Algae [1]	> 200 mg/l (Desmodesmus subspicatus, Literature)

12.2. Persistence and degradability

graphite (7782-42-5)

Not rapidly degradable

talca (14807-96-6)

Not rapidly degradable

Persistence and degradability	Biodegradability in soil: not applicable.
-------------------------------	---

RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

talca (14807-96-6)	
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
Carbamodithioic acid, dibutyl-, methylene ester (10254-57-6)	
Not rapidly degradable	
Octadecanoic acid, 12-hydroxy-, calcium salt (2:1) (3159-62-4)	
Not rapidly degradable	
white mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not rapidly degradable.
chalk (1317-65-3)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

talca (14807-96-6)	
BCF - Other aquatic organisms [1]	3.162 l/kg (BCFBAF v3.01, Fresh water, QSAR)
Partition coefficient n-octanol/water (Log Pow)	-9.4 (QSAR, KOWWIN, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
white mineral oil (petroleum) (8042-47-5)	
Partition coefficient n-octanol/water (Log Pow)	> 6 (calculated value)

12.4. Mobility in soil

talca (14807-96-6)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.5 (log Koc, SRC PCKOCWIN v2.0, QSAR)
white mineral oil (petroleum) (8042-47-5)	
Ecology - soil	Product adsorbs onto the soil.
chalk (1317-65-3)	
Ecology - soil	No (test) data on mobility of the substance available.

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

SECTION 13: Disposal considerations

Regional legislation (waste)	: Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.
Waste treatment methods	: Must follow special treatment according to local regulation.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.




RUN-N-SEAL® EXTREME

Safety Data Sheet

According to ABNT NBR 14725-4

SECTION 14: Transport information

National and international Regulations

RES 5232	IMDG	IATA
UN number		
Not applicable	Not applicable	Not applicable
UN Proper Shipping Name		
Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
Danger labels		
Not applicable	Not applicable	Not applicable
		
Subsidiary risk		
Not applicable	Not applicable	Not applicable
Risk Number		
Not applicable		
Packing group		
Not applicable	Not applicable	Not applicable
Special provisions		
Not applicable	Not applicable	Not applicable
Dangerous for the environment		
Yes	No	No

14.2 Other information

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 229, of 24 May 2011 – Modifies Regulatory Standard no. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5232, of 14 December 2016, approving the supplementary instructions to the Regulation on the Inland Transport of Dangerous Goods and other provisions.

SECTION 16: Other information

No additional information available

Safety Data Sheet (SDS), Brazil

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.