

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : 769 LUBRICANT®  
Product group : Mixtures

#### 1.2. Recommended use and restrictions on use

Recommended use : Lubricants, Greases and Release Products

#### 1.3. Supplier

##### Manufacturer

Whitmore Manufacturing LLC  
930 Whitmore Drive  
Rockwall, Texas, 75087  
USA  
T 1.972.771.1000  
[Regulatory@whitmores.com](mailto:Regulatory@whitmores.com) - [www.jetlube.com](http://www.jetlube.com)

##### Supplier

Jet-Lube of Canada LTD  
Units 8 & 9, 1260 - 34 Avenue  
Nisku, AB, T9E 1K7  
Canada  
T 1.780.463.7441  
[Regulatory@whitmores.com](mailto:Regulatory@whitmores.com) - [www.jetlube.com](http://www.jetlube.com)

#### 1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week  
Within USA and Canada: 1.800.424.9300  
Outside USA and Canada: +1.703.527.3887  
(collect calls accepted)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Flammable liquids Category 4	H227	Combustible liquid
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Full text of H statements : see section 16		

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Danger

Hazard statements (GHS CA)

: H227 - Combustible liquid  
H304 - May be fatal if swallowed and enters airways  
H319 - Causes serious eye irritation

Precautionary statements (GHS CA)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 - Do NOT induce vomiting.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403 - Store in a well-ventilated place.

# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
distillates, hydrotreated light	-	CAS-No.: 64742-47-8	62-67	Flam. Liq. 3, H226 Asp. Tox. 1, H304
paraffin oils (petroleum), catalytic dewaxed light	paraffin oils (petroleum), catalytic dewaxed light	CAS-No.: 64742-71-8	20-25	Not classified
Dodecenylsuccinic acid reaction product	-	CAS-No.: Proprietary	2.37825	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.  
Potential Adverse human health effects and symptoms : Fatal if swallowed.

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Unsuitable extinguishing media

No additional information available

#### 5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.  
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 8.3. Individual protection measures/Personal protective equipment

Hand protection:				
Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	2 (> 30 minutes)	0.3 mm - 0.6 mm	

Skin and body protection:				
Wear suitable protective clothing				

Respiratory protection:				
No respiratory protection needed under normal use conditions				

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: amber
Odor	: petroleum-like odor
Odor threshold	: No data available
pH	: 7
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 81 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 0.0533 kPa
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Slightly soluble, the product remains on the water surface.
Partition coefficient n-octanol/water (Log Pow)	: 3.3 – 6
Viscosity, kinematic	: 4.5 – 8.5 mm <sup>2</sup> /s @ 40°C
Explosion limits	: No data available

### 9.2. Other information

VOC content	: 3.6 %
-------------	---------

## SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -

paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

Dodecenylsuccinic acid reaction product (Proprietary)	
LD50 oral rat	300 – 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CA (oral)	300 mg/kg body weight

Skin corrosion/irritation : Not classified  
pH: 7  
Serious eye damage/irritation : Causes serious eye irritation.  
pH: 7  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified

distillates, hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

distillates, hydrotreated light (64742-47-8)	
NOAEL (oral,rat,90 days)	750 mg/kg body weight Animal: rat, Animal sex: female
NOAEC (inhalation,rat,vapor,90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	≈ 1000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.

769 LUBRICANT®	
Viscosity, kinematic	4.5 – 8.5 mm²/s @ 40°C
distillates, hydrotreated light (64742-47-8)	
Viscosity, kinematic	1.97 mm²/s (25 °C)
Animal studies and expert judgment for classification	False

# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
Viscosity, kinematic	1.99 – 847 mm <sup>2</sup> /s Temp.: '40°C' Parameter: 'mm <sup>2</sup> /s' 'mm <sup>2</sup> /s'
Animal studies and expert judgment for classification	False
Dodecenylsuccinic acid reaction product (Proprietary)	
Animal studies and expert judgment for classification	False
Potential Adverse human health effects and symptoms	: Fatal if swallowed.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

769 LUBRICANT®	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6
distillates, hydrotreated light (64742-47-8)	
LC50 - Fish [1]	2.2 mg/l
EC50 - Crustacea [1]	> 100 mg/l (Invertebrata)

### 12.2. Persistence and degradability

distillates, hydrotreated light (64742-47-8)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

769 LUBRICANT®	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6
distillates, hydrotreated light (64742-47-8)	
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
Partition coefficient n-octanol/water (Log Pow)	6 – 8.2

### 12.4. Mobility in soil

distillates, hydrotreated light (64742-47-8)	
Surface tension	0.026 N/m (20 °C)
Ecology - soil	Adsorbs into the soil.

### 12.5. Other adverse effects

Ozone	: Not classified
-------	------------------

# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

#### 14.1. UN number

UN-No. (TDG)	: Not applicable
DOT NA No	: NA1993
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable

#### 14.2. UN proper shipping name

Proper Shipping Name (TDG)	: Not applicable
Proper Shipping Name (DOT)	: Combustible liquid, n.o.s.
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable

#### 14.3. Transport hazard class(es)

##### TDG

Transport hazard class(es) (TDG) : Not applicable

##### DOT

Transport hazard class(es) (DOT) : Combustible liquid

##### IMDG

Transport hazard class(es) (IMDG) : Not applicable

##### IATA

Transport hazard class(es) (IATA) : Not applicable

#### 14.4. Packing group

Packing group (TDG)	: Not applicable
Packing group (DOT)	: III
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

##### TDG

No data available

##### DOT

UN-No.(DOT) : NA1993

# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT Special Provisions (49 CFR 172.102)	: 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e., a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### IMDG

No data available

### IATA

No data available

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)

Listed on the Canadian DSL (Domestic Substances List)

Canada DSL & NDSL Flags

Substance was manufactured or imported after July 1, 1995

### 15.2. International regulations

distillates, hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)



# 769 LUBRICANT®

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Dodecenylsuccinic acid reaction product (Proprietary)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

### SECTION 16: Other information

Issue date : 12-10-2020  
Revision date : 07-11-2022  
Supersedes : 12-10-2020

#### Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.