

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Trade name : FOOD GRADE SILICONE AEROSOL
Product group : Trade product

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Manufacturer

Whitmore Manufacturing LLC
930 Whitmore Drive
Rockwall, Texas, 75087
USA
T 1.972.771.1000
Regulatory@whitmores.com - www.jetlube.com

Distributor

Jet-Lube of Canada LTD
Units 8 & 9, 1260 - 34 Avenue
Nisku, AB, T9E 1K7
Canada
T 1.780.463.7441
Regulatory@whitmores.com - www.jetlube.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week
Within USA and Canada: 1.800.424.9300
Outside USA and Canada: +1.703.527.3887
(collect calls accepted)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA)



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : H222 - Extremely flammable aerosol
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
acetone	2-propanon / 2-propanone / acetone / acetone NF / acetone oil / A13-01238 / Caswell No.004 / chevron acetone / dimethyl formaldehyde / dimethyl ketone / dimethylketal / Dimethylketon / DMK (=dimethyl ketone) / FEMA No 3326 / ketone propane / KTI acetone / methyl acetyl / pyroacetic acid / pyroacetic ether / pyroacetic spirit / STEC 4908105	CAS-No.: 67-64-1	40.5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
heptane	alkane C7 / ASTM normal-heptane knock test reference fuel / dipropylmethane / dipropylmethane (=normal-heptane) / ESSO heptane / gettysolve-C / heptane / heptane, anhydrous / heptyl hydride / hexylmethane / HYDROSOL-HEPTANE / methylhexane / n-dipropylmethane / n-heptane / n-heptyl hydride / normal-dipropylmethane / normal-heptane / normal-heptyl hydride / NORPAR 7 / protein sequencer reagent S1 / SBP 94/99 / skellysolve C / solvent heptane	CAS-No.: 142-82-5	15.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Neoprene or nitrile rubber gloves

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	2 (> 30 minutes)	0.3 mm - 0.6 mm	

Eye protection:

Wear eye protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Colourless to light yellow liquid
Odor	: mild
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 60 °C
Flash point	: < -18 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 1
Explosion limits	: No data available

9.2. Other information

Gas group	: Compressed gas
-----------	------------------

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
ATE CA (oral)	5800 mg/kg body weight
ATE CA (Dermal)	20000 mg/kg body weight

heptane (142-82-5)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 29.29 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	> 29.29 mg/l Source: ECHA

Skin corrosion/irritation : Causes skin irritation.

acetone (67-64-1)	
pH	7 (10 g/l)

Serious eye damage/irritation : Causes serious eye irritation.

acetone (67-64-1)	
pH	7 (10 g/l)

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)

STOT-single exposure : May cause drowsiness or dizziness.

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

heptane (142-82-5)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

heptane (142-82-5)	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male

Aspiration hazard : Not classified

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

FOOD GRADE SILICONE AEROSOL	
Vaporizer	Aerosol
acetone (67-64-1)	
Viscosity, kinematic	0.417 mm²/s
Animal studies and expert judgment for classification	False
heptane (142-82-5)	
Viscosity, kinematic	0.641 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
Animal studies and expert judgment for classification	False
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects

acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 96h - Algae [1]	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
heptane (142-82-5)	
LC50 - Fish [1]	5.738 mg/l Source: QSAR
EC50 - Crustacea [1]	0.1 mg/l
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

acetone (67-64-1)	
Not rapidly degradable	
Persistence and degradability	Biodegradable in the soil;Biodegradable in the soil under anaerobic conditions;Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)
heptane (142-82-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.92 g O ₂ /g substance

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

heptane (142-82-5)	
Chemical oxygen demand (COD)	0.06 g O ₂ /g substance
ThOD	3.52 g O ₂ /g substance
BOD (% of ThOD)	> 0.5 (5 day(s), Literature study)

12.3. Bioaccumulative potential

acetone (67-64-1)	
Bioaccumulative potential	Not bioaccumulative.
BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)

heptane (142-82-5)	
Bioaccumulative potential	Potential for bioaccumulation ($4 \geq \text{Log Kow} \leq 5$).
BCF - Other aquatic organisms [1]	552 (BCFBAF v3.00, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	4.66 (Experimental value)

12.4. Mobility in soil

acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test) data on mobility of the substance available.

heptane (142-82-5)	
Mobility in soil	239.7 Source: ECHA
Surface tension	19.66 mN/m (25 °C)
Ecology - soil	Low potential for adsorption in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information





In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN number			
UN1950	1950	1950	1950
14.2. Proper Shipping Name			
AEROSOLS	Aerosols	AEROSOLS	Aerosols, flammable

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

TDG	DOT	IMDG	IATA
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

TDG

UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

DOT

UN-No.(DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

IATA

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

heptane (142-82-5)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

FOOD GRADE SILICONE AEROSOL

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

heptane (142-82-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

SECTION 16: Other information

Issue date	: 07-08-2022
Revision date	: 02-03-2023
Supersedes	: 11-17-2022

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor

FOOD GRADE SILICONE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of H-phrases:	
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.