



# Gear Oil FG ISO 680

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 2022-07-15 Revision date: 2023-04-19 Supersedes: 2022-08-10 Version: 1.2

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Gear Oil FG ISO 680  
Product group : Mixtures

#### 1.2. Recommended use and restrictions on use

Recommended use : Lubricants, Greases and Release Products

#### 1.3. Supplier

##### Manufacturer

Whitmore Manufacturing LLC  
930 Whitmore Drive  
Rockwall, Texas, 75087  
USA

T 1.972.771.1000

[Regulatory@whitmores.com](mailto:Regulatory@whitmores.com) - [www.jetlube.com](http://www.jetlube.com)

##### Distributor

Jet-Lube of Canada LTD  
Units 8 & 9, 1260 - 34 Avenue  
Nisku, AB, T9E 1K7  
Canada

T 1.780.463.7441

[Regulatory@whitmores.com](mailto:Regulatory@whitmores.com) - [www.jetlube.com](http://www.jetlube.com)

#### 1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week  
Within USA and Canada: 1.800.424.9300  
Outside USA and Canada: +1.703.527.3887  
(collect calls accepted)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Not classified

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

No labeling applicable

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

# Gear Oil FG ISO 680

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Butene, homopolymer	butene, homopolymer (products derived from either/or But- 1-ene/But-2-ene) (consisting of 50 wt % or more of species of the same m. wt.) / butylene oligomers C16 and higher	CAS-No.: 9003-29-6	23.89	Flam. Liq. 2, H225 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

No additional information available

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Unsuitable extinguishing media

No additional information available

### 5.3. Specific hazards arising from the hazardous product

No additional information available

### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

# Gear Oil FG ISO 680

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

<b>Hand protection:</b>				
Neoprene or nitrile rubber gloves				
Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	2 (> 30 minutes)	0.3 mm - 0.6 mm	

<b>Eye protection:</b>
Wear eye protection

<b>Skin and body protection:</b>
Wear suitable protective clothing

<b>Respiratory protection:</b>
No respiratory protection needed under normal use conditions

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.

# Gear Oil FG ISO 680

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Color	: amber
Odor	: petroleum-like odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 205 °C Cleveland Open Cup Method
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 661 mm <sup>2</sup> /s @ 40 °C
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

Reactivity	: No additional information available
Chemical stability	: No additional information available
Possibility of hazardous reactions	: No additional information available
Conditions to avoid	: No additional information available
Incompatible materials	: No additional information available
Hazardous decomposition products	: No additional information available
Hardening time:	: No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Butene, homopolymer (9003-29-6)	
LD50 oral rat	> 10000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 19.171 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
LC50 Inhalation - Rat [ppm]	> 4185 ppm (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))

Skin corrosion/irritation	: Not classified
---------------------------	------------------

Butene, homopolymer (9003-29-6)	
pH	Not applicable

Serious eye damage/irritation	: Not classified
-------------------------------	------------------

Butene, homopolymer (9003-29-6)	
pH	Not applicable

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

# Gear Oil FG ISO 680

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified

Butene,homopolymer (9003-29-6)	
LOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: other:OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, vapor, 90 days)	1 mg/l air Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified.

Gear Oil FG ISO 680	
Viscosity, kinematic	661 mm <sup>2</sup> /s @ 40 °C
Butene,homopolymer (9003-29-6)	
Viscosity, kinematic	1.66 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
Animal studies and expert judgment for classification	False

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Butene,homopolymer (9003-29-6)	
LC50 - Fish [1]	0.037 mg/l Test organisms (species): other:Fish, no other information
LC50 - Fish [2]	0.0011 – 1.19 mg/l Test organisms (species): other:Fish, no other information
EC50 - Crustacea [1]	> 3.1 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	0.04 mg/l Test organisms (species): other:Daphnid no other information.
EC50 72h - Algae [1]	> 19.2 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Butene,homopolymer (9003-29-6)	
Bioaccumulative potential	Potential for bioaccumulation ( $500 \leq \text{BCF} \leq 5000$ ).
BCF - Other aquatic organisms [1]	314 – 1882 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	17.14 Source: Quantitative Structure Activity Relation

### 12.4. Mobility in soil

Butene,homopolymer (9003-29-6)	
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.44 – 8.13 (log Koc, Calculated value)

### 12.5. Other adverse effects

Ozone : Not classified

# Gear Oil FG ISO 680

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
<b>14.1. UN number</b>			
Not regulated for transport			
<b>14.2. Proper Shipping Name</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

#### 14.6. Special precautions for user

##### TDG

No data available

##### DOT

No data available

##### IMDG

No data available

##### IATA

No data available

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# Gear Oil FG ISO 680

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 15: Regulatory information

#### 15.1. National regulations

Butene, homopolymer (9003-29-6)

Listed on the Canadian DSL (Domestic Substances List)

#### 15.2. International regulations

Gear Oil FG ISO 680

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Butene, homopolymer (9003-29-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### SECTION 16: Other information

Issue date : 07-15-2022  
Revision date : 04-19-2023  
Supersedes : 08-10-2022

#### Full text of H-phrases:

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.