

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Trade name : JET-LOK III - Side B
 Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Adhesives, sealants

1.3. Supplier

Manufacturer

Jet-Lube
 930 Whitmore Drive
 75087 Rockwall, Texas - USA
 T 1.972.771.1000
Regulatory@whitmores.com - www.jetlube.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week
 Within USA and Canada: 1.800.424.9300
 Outside USA and Canada: +1.703.527.3887
 (collect calls accepted)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA) : 

Signal word (GHS CA) : Warning

Hazard statements (GHS CA) : H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS CA) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P314 - Get medical advice/attention if you feel unwell.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

JET-LOK III - Side B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
epoxy resins, liquids, MM≤700	epoxy resin(=araldite gy250) / reaction product: bisphenol-A-(epichlorhydrin)	CAS-No.: 25068-38-6	97.5 – 99.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 2, H373

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
First-aid measures general : Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

JET-LOK III - Side B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

JET-LOK III - Side B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: amber
Odour	: Amine-like Ammonia odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 117 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1 g/m ³
Solubility	: Water: Slightly soluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

JET-LOK III - Side B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

epoxy resins, liquids, MM≤700 (25068-38-6)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

epoxy resins, liquids, MM≤700 (25068-38-6)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

epoxy resins, liquids, MM≤700 (25068-38-6)	
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

epoxy resins, liquids, MM≤700 (25068-38-6)	
LC50 - Fish [1]	1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.7 mg/l
EC50 72h - Algae [1]	9.4 mg/l Test organisms (species): Scenedesmus capricornutum

JET-LOK III - Side B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

epoxy resins, liquids, MM≤700 (25068-38-6)	
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
BCF - Other aquatic organisms [1]	31 (Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

epoxy resins, liquids, MM≤700 (25068-38-6)	
Persistence and degradability	Non degradable in the soil.

12.3. Bioaccumulative potential

epoxy resins, liquids, MM≤700 (25068-38-6)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Other aquatic organisms [1]	31 (Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)

12.4. Mobility in soil

epoxy resins, liquids, MM≤700 (25068-38-6)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Ecology - soil	Low potential for adsorption in soil.
Partition coefficient n-octanol/water (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

JET-LOK III - Side B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : Not applicable

DOT

Transport hazard class(es) (DOT) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (TDG) : Not applicable

Packing group (DOT) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

TDG

No data available

DOT

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

epoxy resins, liquids, MM \leq 700 (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

epoxy resins, liquids, MM \leq 700 (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Issue date : 12/11/2020

Revision date : 01/29/2021

Supersedes : 12/11/2020

JET-LOK III - Side B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of H-statements:	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.