

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JET-LOK III Side A - Epoxy Base  
Product group : Trade product

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

##### Manufacturer

Whitmore Manufacturing LLC  
930 Whitmore Drive  
Rockwall, Texas, 75087  
USA  
T 1.972.771.1000  
[Regulatory@whitmores.com](mailto:Regulatory@whitmores.com) - [www.jetlube.com](http://www.jetlube.com)

##### Distributor

Jet-Lube of Canada LTD  
Units 8 & 9, 1260 - 34 Avenue  
Nisku, AB, T9E 1K7  
Canada  
T 1.780.463.7441  
[Regulatory@whitmores.com](mailto:Regulatory@whitmores.com) - [www.jetlube.com](http://www.jetlube.com)

#### 1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week  
Within USA and Canada: 1.800.424.9300  
Outside USA and Canada: +1.703.527.3887  
(collect calls accepted)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Full text of H statements : see section 16		

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Warning

Hazard statements (GHS CA)

: H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

Precautionary statements (GHS CA)

: P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
epoxy resins, liquids, MM≤700	epoxy resin(=araldite gy250) / reaction product: bisphenol-A-(epichlorhydrin)	CAS-No.: 25068-38-6	20.1678 – 21.359	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
calcium sulfate	anhydrous gypsum / anhydrous sulfate of lime / basic calcium sulfate / calcium sulfate / calcium sulfate (1:1) / calcium sulfate (CaSO <sub>4</sub> ) / calcium sulfate, anhydrous / calcium sulfate, natural / calcium sulphate / crysalba / dead- burned gypsum / drierite / E516 / Franklin fiber H45 / gibs / gypsum, anhydrous / karstenite / muriacite / natural anhydrite / oparex 10 / osteoset / pigment white 25 / satin white / sikkon fluka universal desiccant / SSS-A / sulfate of lime / sulfate of lime, anhydrous / sulfuric acid calcium salt / sulfuric acid calcium(2+) salt (1:1) / sulfuric acid, calcium salt (1:1) / terra alba / thiolite	CAS-No.: 7778-18-9	14.9	Acute Tox. 4 (Oral), H302

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

#### 5.2. Unsuitable extinguishing media

No additional information available

#### 5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.  
Additional hazards when processed : Use Caution when mixing: Generation of heat before curing.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 8.3. Individual protection measures/Personal protective equipment

#### Materials for protective clothing:

Wear protective clothing

#### Hand protection:

Neoprene or nitrile rubber gloves

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	6 (> 480 minutes)	> 0.6 mm	

#### Eye protection:

Wear eye protection

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

No respiratory protection needed under normal use conditions

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Color	: Gray
Odor	: Mild odour
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: > 160 °C
Flash point	: > 160 °C
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: 80000 mPa·s
Explosion limits	: Not applicable

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>calcium sulfate (7778-18-9)</b>	
LD50 oral rat	> 1581 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LC50 Inhalation - Rat	> 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
ATE CA (oral)	500 mg/kg body weight

<b>epoxy resins, liquids, MM≤700 (25068-38-6)</b>	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Skin corrosion/irritation	: Causes skin irritation.
---------------------------	---------------------------

<b>calcium sulfate (7778-18-9)</b>	
pH	6 – 7.6 (20 %)

Serious eye damage/irritation	: Causes serious eye irritation.
-------------------------------	----------------------------------

<b>calcium sulfate (7778-18-9)</b>	
pH	6 – 7.6 (20 %)

Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>calcium sulfate (7778-18-9)</b>	
NOAEL (chronic,oral,animal/male,2 years)	256 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	284 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)

<b>epoxy resins, liquids, MM≤700 (25068-38-6)</b>	
NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

calcium sulfate (7778-18-9)	
LOAEL (oral, rat, 90 days)	237 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	79 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

epoxy resins, liquids, MM≤700 (25068-38-6)	
NOAEL (oral, rat, 90 days)	50 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other: japanese MITI guidelines for toxicity testing of chemicals

Aspiration hazard : Not classified

JET-LOK III Side A - Epoxy Base	
Viscosity, kinematic	Not applicable

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects

calcium sulfate (7778-18-9)	
LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oryzias latipes
EC50 72h - Algae [1]	> 79 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	3200 mg/l Source: ECOTOX

epoxy resins, liquids, MM≤700 (25068-38-6)	
LC50 - Fish [1]	1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.7 mg/l
EC50 72h - Algae [1]	9.4 mg/l Test organisms (species): Scenedesmus capricornutum
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

calcium sulfate (7778-18-9)	
Not rapidly degradable	
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

epoxy resins, liquids, MM≤700 (25068-38-6)	
Not rapidly degradable	
Persistence and degradability	Not degradable in the soil.

### 12.3. Bioaccumulative potential

calcium sulfate (7778-18-9)	
Bioaccumulative potential	No bioaccumulation data available.
epoxy resins, liquids, MM≤700 (25068-38-6)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Other aquatic organisms [1]	31 (Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)

### 12.4. Mobility in soil

epoxy resins, liquids, MM≤700 (25068-38-6)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)

### 12.5. Other adverse effects

Ozone : Not classified

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			



# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 14.6. Special precautions for user

#### TDG

Not regulated

#### DOT

Not regulated

#### IMDG

Not regulated

#### IATA

Not regulated

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### calcium sulfate (7778-18-9)

Listed on the Canadian DSL (Domestic Substances List)

#### epoxy resins, liquids, MM≤700 (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

### 15.2. International regulations

#### JET-LOK III Side A - Epoxy Base

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

#### calcium sulfate (7778-18-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

#### epoxy resins, liquids, MM≤700 (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## SECTION 16: Other information

Issue date : 12-10-2020  
Revision date : 11-20-2023  
Supersedes : 01-20-2021

# JET-LOK III Side A - Epoxy Base

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### Full text of H-phrases:

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.