

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 14/07/2022 Revision date: 07/12/2023 Supersedes version of: 17/11/2023 Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

 Trade name
 : C-PLATE™ AEROSOL

 UFI
 : 3NT0-00A4-S00G-YSK0

Vaporizer : Aerosol
Product group : Mixtures

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer Distributor

Whitmore Manufacturing LLC
930 Whitmore Drive
Whitmore Europe Limited
Unit 9

75087 Rockwall, Texas Foster Avenue, Woodside Park Industrial Estate

USA Dunstable, Bedfordshire , LU5 5TA T 1.972.771.1000 United Kingdom

Regulatory@whitmores.com - www.jetlube.com T +44 1707 379870

Regulatory@whitmores.com - www.whitmores.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week

Within USA and Canada: 1.800.424.9300 Outside USA and Canada: +1.703.527.3887

(collect calls accepted)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	Chemtrec - United Kingdom	London	Local (City) +44 20 3807 3798	
United Kingdom	Chemtrec - United Kingdom		Local (National) +44 870 820 0418	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Edinburgh Centre) Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis

07/12/2023 (Revision date) GB - en 1/30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment - Acute Hazard,

H400

Category 1

Hazardous to the aquatic environment – Chronic Hazard,

H410

Category 1

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

: Danger

GHS07

GHS09

Signal word (CLP)

Contains

: acetone; Methyl ethyl ketone

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTRE or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component		
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Methyl ethyl ketone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
copper (7440-50-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
2-phenoxyethanol (122-99-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Component		
Ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
toluene (108-88-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
methyl propyl ketone (107-87-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Methyl isobutyl ketone (108-10-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
cobalt(II) 2-ethylhexanoate (136-52-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
cyclohexane (110-82-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
butyl glycolether (111-76-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
N-methyl-2-pyrrolidone (872-50-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Cumene (98-82-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
N-methyl-2-pyrrolidone(872-50-4)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

3.2. Mixtures			
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5	26	Flam. Gas 1A, H220 Aerosol 1, H222;H229 Press. Gas Aquatic Chronic 2, H411
acetone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8	24.79	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	18.324472 – 18.546472	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Aquatic Chronic 2, H411
Methyl ethyl ketone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3	16.2726	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
copper substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 7440-50-8 EC-No.: 231-159-6 EC Index-No.: 029-024-00-X	4.07	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methyl propyl ketone substance with national workplace exposure limit(s) (GB)	CAS-No.: 107-87-9 EC-No.: 203-528-1	1.5392	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
N-methyl-2-pyrrolidone substance listed as REACH Candidate (1-Methyl-2- pyrrolidone (NMP)) substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 872-50-4 EC-No.: 212-828-1 EC Index-No.: 606-021-00-7	0.216672 – 0.221186	Not classified
Ethylbenzene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	0.135568 - 0.209568	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
cobalt(II) 2-ethylhexanoate substance with national workplace exposure limit(s) (GB)	CAS-No.: 136-52-7 EC-No.: 205-250-6	0.13949 – 0.16095	Not classified
butyl glycolether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0	0.10101 – 0.11655	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373
cyclohexane substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 110-82-7 EC-No.: 203-806-2 EC Index-No.: 601-017-00-1	0.066526 - 0.087986	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Methyl isobutyl ketone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-10-1 EC-No.: 203-550-1 EC Index-No.: 606-004-00-4	0.084656	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335
naphtha (petroleum), hydrotreated heavy substance with a Community workplace exposure limit (Note P)	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6	0.0296 – 0.03552	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
toluene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	0.00074 – 0.0074	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 1, H410
Cumene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 98-82-8 EC-No.: 202-704-5 EC Index-No.: 601-024-00-X	0.00074 – 0.0074	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Aquatic Chronic 2, H411

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
N-methyl-2-pyrrolidone	CAS-No.: 872-50-4 EC-No.: 212-828-1 EC Index-No.: 606-021-00-7	(10 ≤ C ≤ 100) STOT SE 3, H335

Note P:

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Exercise caution. Spill area may be slippery. No open flames, no sparks, and no smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn,

even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal

protective equipment

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store

locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

07/12/2023 (Revision date) GB - en 5/30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

8.1.1 National occupational exposure and biological limit values		
naphtha (petroleum), hydrotreated heavy (64742-48-9)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	White spirit Type 3	
IOEL TWA	116 mg/m³	
IOEL TWA [ppm]	20 ppm	
IOEL STEL	290 mg/m³	
IOEL STEL [ppm]	50 ppm	
Remark	Skin. (Year of adoption 2007)	
Regulatory reference	SCOEL Recommendations	
acetone (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetone	
IOEL TWA	1210 mg/m³	
IOEL TWA [ppm]	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Acetone	
WEL TWA (OEL TWA) [1]	1210 mg/m³	
WEL TWA (OEL TWA) [2]	500 ppm	
WEL STEL (OEL STEL)	3620 mg/m³	
WEL STEL (OEL STEL) [ppm]	1500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Xylene (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Xylene, mixed isomers, pure	
IOEL TWA	221 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Xylene	
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers	
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom - Biological limit values		
Local name	Xylene, o-, m-, p- or mixed isomers	

07/12/2023 (Revision date) GB - en 6/30

Safety Data Sheet

Xylene (1330-20-7)			
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
Methyl ethyl ketone (78-93-3)	Methyl ethyl ketone (78-93-3)		
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Butanone		
IOEL TWA	600 mg/m³		
IOEL TWA [ppm]	200 ppm		
IOEL STEL	900 mg/m³		
IOEL STEL [ppm]	300 ppm		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	Butan-2-one (methyl ethyl ketone)		
WEL TWA (OEL TWA) [1]	600 mg/m³		
WEL TWA (OEL TWA) [2]	200 ppm		
WEL STEL (OEL STEL)	899 mg/m³		
WEL STEL (OEL STEL) [ppm]	300 ppm		
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
United Kingdom - Biological limit values			
Local name	Butan-2-one (methyl ethyl ketone)		
BMGV	70 μmol/l Parameter: butan-2-one - Medium: urine - Sampling time: Post shift		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
copper (7440-50-8)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Copper Kobber		
IOEL TWA	0.01 mg/m³ (respirable fraction)		
Remark	(Year of adoption 2014) (Adopsjonsår 2014)		
Regulatory reference	SCOEL Recommendations SCOEL anbefalinger		
United Kingdom - Occupational Exposure Limits			
Local name	Copper		
WEL TWA (OEL TWA) [1]	0.2 mg/m³ 1 mg/m³		
WEL STEL (OEL STEL)	2 mg/m³		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
Ethylbenzene (100-41-4)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Ethylbenzene		
IOEL TWA	442 mg/m³		
IOEL TWA [ppm]	100 ppm		
IOEL STEL	884 mg/m³		

Safety Data Sheet

Ethylbenzene (100-41-4)		
IOEL STEL [ppm]	200 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Ethylbenzene	
WEL TWA (OEL TWA) [1]	441 mg/m³	
WEL TWA (OEL TWA) [2]	100 ppm	
WEL STEL (OEL STEL)	552 mg/m³	
WEL STEL (OEL STEL) [ppm]	125 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
toluene (108-88-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Toluene	
IOEL TWA	192 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	384 mg/m³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Toluene	
WEL TWA (OEL TWA) [1]	191 mg/m³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	384 mg/m³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
methyl propyl ketone (107-87-9)		
United Kingdom - Occupational Exposure Limits		
Local name	Pentan-2-one	
WEL TWA (OEL TWA) [1]	716 mg/m³	
WEL TWA (OEL TWA) [2]	200 ppm	
WEL STEL (OEL STEL)	895 mg/m³	
WEL STEL (OEL STEL) [ppm]	250 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Methyl isobutyl ketone (108-10-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	4-Methylpentan-2-one	
IOEL TWA	83 mg/m³	
IOEL TWA [ppm]	20 ppm	
IOEL STEL	208 mg/m³	

Safety Data Sheet

Methyl isobutyl ketone (108-10-1)			
IOEL STEL [ppm]	50 ppm		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	4-Methylpentan-2-one		
WEL TWA (OEL TWA) [1]	208 mg/m³		
WEL TWA (OEL TWA) [2]	50 ppm		
WEL STEL (OEL STEL)	416 mg/m³		
WEL STEL (OEL STEL) [ppm]	100 ppm		
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
United Kingdom - Biological limit values			
Local name	4-methylpentan-2-one		
BMGV	20 μmol/l Parameter: 4-methylpentan-2-one - Medium: urine - Sampling time: Post shift		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
cobalt(II) 2-ethylhexanoate (136-52-7)			
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	0.1 mg/m³		
cyclohexane (110-82-7)			
EU - Indicative Occupational Exposure Limit (IOEL			
Local name	Cyclohexane		
IOEL TWA	700 mg/m³		
IOEL TWA [ppm]	200 ppm		
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC		
United Kingdom - Occupational Exposure Limits			
Local name	Cyclohexane		
WEL TWA (OEL TWA) [1]	350 mg/m³		
WEL TWA (OEL TWA) [2]	100 ppm		
WEL STEL (OEL STEL)	1050 mg/m³		
WEL STEL (OEL STEL) [ppm]	300 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
butyl glycolether (111-76-2)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	2-Butoxyethanol		
IOEL TWA	98 mg/m³		
IOEL TWA [ppm]	20 ppm		
IOEL STEL	246 mg/m³		
IOEL STEL [ppm]	50 ppm		
Remark	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	2-Butoxyethanol		
WEL TWA (OEL TWA) [1]	123 mg/m³		

Safety Data Sheet

butyl glycolether (111-76-2)		
WEL TWA (OEL TWA) [2]	25 ppm	
WEL STEL (OEL STEL)	246 mg/m³	
WEL STEL (OEL STEL) [ppm]	50 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom - Biological limit values		
Local name	2-Butoxyethanol	
BMGV	240 mmol/mol Creatinine Parameter: butoxyacetic acid - Medium: urine - Sampling time: Post shift	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
N-methyl-2-pyrrolidone (872-50-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Methyl-2-pyrrolidone	
IOEL TWA	40 mg/m³	
IOEL TWA [ppm]	10 ppm	
IOEL STEL	80 mg/m³	
IOEL STEL [ppm]	20 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU	
EU - Biological Limit Value (BLV)		
Local name	N-Methyl-2-pyrrolidone	
BLV	20 mg/g creatinine Parameter: 2-hydroxy-N-methylsuccinimide - Medium: urine - Sampling time: morning-after-shift; 18 hours 70 mg/g creatinine Parameter: 5-hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: 2-4 hours after the end of exposure/shift	
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs	
United Kingdom - Occupational Exposure Limits		
Local name	n-Methyl-2-pyrrolidone	
WEL TWA (OEL TWA) [1]	40 mg/m³	
WEL TWA (OEL TWA) [2]	10 ppm	
WEL STEL (OEL STEL)	80 mg/m³	
WEL STEL (OEL STEL) [ppm]	20 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Cumene (98-82-8)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	2-Phenylpropane (Cumene)	
IOEL TWA	50 mg/m³	
IOEL TWA [ppm]	10 ppm	
IOEL STEL	250 mg/m³	
IOEL STEL [ppm]	50 ppm	
Remark	Skin. During exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Cumene (98-82-8)		
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831	
United Kingdom - Occupational Exposure Limits		
Local name	Cumene	
WEL TWA (OEL TWA) [1]	125 mg/m³	
WEL TWA (OEL TWA) [2]	25 ppm	
WEL STEL (OEL STEL)	250 mg/m³	
WEL STEL (OEL STEL) [ppm]	50 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Wear eye protection

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Neoprene or nitrile rubber gloves

Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes)	> 0.6 mm		
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Hand protection					

Other skin protection

Materials for protective clothing:

Wear protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Metallic.

Appearance : Liquefied compressed gas.

Odour: solvent-like.Odour threshold: Not availableMelting point: Not applicableFreezing point: Not availableBoiling point: Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit : Not available Upper explosion limit : Not available Flash point : -20 °C Auto-ignition temperature : Not available Decomposition temperature : Not available : Not available : Not available Viscosity, kinematic Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available : 880.72 g/l Density : Not available Relative density Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 87.853788 %

9.2.2. Other safety characteristics

Gas group : Press. Gas (Liq.)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Safety Data Sheet

naphtha (petroleum), hydrotreated heavy ((64742-48-9)
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LD50 dermal	1700 mg/kg
LC50 Inhalation - Rat (Vapours)	27.57 mg/l/4h
Methyl ethyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Readacross, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat (Vapours)	34.5 mg/l/4h
copper (7440-50-8)	
LD50 oral rat	> 2500 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5.11 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation)
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
toluene (108-88-3)	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	25.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	12.5 mg/l/4h
methyl propyl ketone (107-87-9)	
LD50 oral rat	1600 – 3200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 25.5 mg/l air Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyl isobutyl ketone (108-10-1)	
LD50 oral rat	2080 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1,91 - 2,27
LD50 dermal rat	≥ 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LD50 dermal rabbit	≥ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	11.6 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapours)	8.2 – 16.4 mg/l Source: NTP TR 538
cobalt(II) 2-ethylhexanoate (136-52-7)	
LD50 oral rat	3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2000 mg/kg
cyclohexane (110-82-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 32.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301
LD50 oral	470 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	220 mg/kg
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	2.03 mg/l/4h
N-methyl-2-pyrrolidone (872-50-4)	
LD50 oral rat	4150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 3100 - 5560
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 5.1 mg/l Source: ECHA
Propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
Cumene (98-82-8)	
LD50 oral rat	2700 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 014 day(s))
LD50 oral	2700 mg/kg
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	39 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
LC50 Inhalation - Rat (Vapours)	9.83 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.

Skin corrosion/irritation : Causes skin irritation.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetone (67-64-1)	
pH	7 (10 g/l)
copper (7440-50-8)	1. (1.5 3.1)
pH	No data available in the literature
toluene (108-88-3)	140 data available in the incrature
	7 Source: chemicalbook
pH	7 Source, Chemicalbook
methyl propyl ketone (107-87-9)	No data available is the literature
рН	No data available in the literature
Methyl isobutyl ketone (108-10-1)	
рН	5.4 (14.1 g/l, 20 °C)
cobalt(II) 2-ethylhexanoate (136-52-7)	
pH	6.8 (4.03 %, 20 °C, OECD 105: Water Solubility)
cyclohexane (110-82-7)	
pH	7 (52 mg/l, 23.5 °C)
N-methyl-2-pyrrolidone (872-50-4)	
рН	8 – 10 (10 %)
Propane (74-98-6)	
pH	Not applicable
Serious eye damage/irritation	: Causes serious eye irritation.
acetone (67-64-1)	
рН	7 (10 g/l)
copper (7440-50-8)	
рН	No data available in the literature
toluene (108-88-3)	
pH	7 Source: chemicalbook
methyl propyl ketone (107-87-9)	
pH	No data available in the literature
Methyl isobutyl ketone (108-10-1)	
рН	5.4 (14.1 g/l, 20 °C)
cobalt(II) 2-ethylhexanoate (136-52-7)	
рН	6.8 (4.03 %, 20 °C, OECD 105: Water Solubility)
cyclohexane (110-82-7)	
рН	7 (52 mg/l, 23.5 °C)
N-methyl-2-pyrrolidone (872-50-4)	
рН	8 – 10 (10 %)
Propane (74-98-6)	
pH	Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Xylene (1330-20-7)	
IARC group	3 - Not classifiable

07/12/2023 (Revision date) GB - en 15/30

Safety Data Sheet

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
toluene (108-88-3)	
IARC group	3 - Not classifiable
Methyl isobutyl ketone (108-10-1)	
IARC group	2B - Possibly carcinogenic to humans
butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable
Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
N-methyl-2-pyrrolidone (872-50-4)	
NOAEL (chronic, oral, animal/male, 2 years) NOAEL (chronic, oral, animal/female, 2 years)	≈ 89 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity), Remarks on results: other:Effect type: toxicity (migrated information) ≈ 221 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: OECD Guideline
NOALL (CHOIRC, Grai, anima/remale, 2 years)	451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity), Remarks on results: other:Effect type: toxicity (migrated information)
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met)
acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	May cause drowsiness or dizziness.
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Methyl ethyl ketone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Methyl isobutyl ketone (108-10-1)	
STOT-single exposure	May cause respiratory irritation.
cyclohexane (110-82-7)	
STOT-single exposure	May cause drowsiness or dizziness.
Cumene (98-82-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met)
Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.

Safety Data Sheet

toluene (108-88-3)	
,	4050 may the photocolists Asimal and Ocidation FUNDath and Diccolis Ocidation
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).
Methyl isobutyl ketone (108-10-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
butyl glycolether (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
N-methyl-2-pyrrolidone (872-50-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	1 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (dermal, rat/rabbit, 90 days)	826 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.5 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
C-PLATE™ AEROSOL	
Vaporizer	Aerosol
naphtha (petroleum), hydrotreated heavy (64	742-48-9)
Viscosity, kinematic	< 1 mm²/s Temp.: 'other:37.8°C' Parameter: 'kinematic viscosity (in mm²/s)'
acetone (67-64-1)	
Viscosity, kinematic	0.417 mm²/s
Xylene (1330-20-7)	
Viscosity, kinematic	0.74 mm²/s (20 °C)
Methyl ethyl ketone (78-93-3)	` <u></u>
Viscosity, kinematic	0.494 mm²/s
copper (7440-50-8)	
Viscosity, kinematic	Not applicable (solid)
Ethylbenzene (100-41-4)	
Viscosity, kinematic	0.773 mm²/s (20 °C, OECD 114: Viscosity of Liquids)
toluene (108-88-3)	
Viscosity, kinematic	0.69 mm ² /s (20 °C)
methyl propyl ketone (107-87-9)	
Viscosity, kinematic	No data available in the literature
,,	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyl isobutyl ketone (108-10-1)		
Viscosity, kinematic	0.001 mm²/s (25 °C, Calculated)	
cyclohexane (110-82-7)		
Viscosity, kinematic	0 mm²/s (26 °C)	
butyl glycolether (111-76-2)		
Viscosity, kinematic	2.284 mm²/s (40 °C)	
N-methyl-2-pyrrolidone (872-50-4)		
Viscosity, kinematic	1.7 mm²/s (25 °C)	
Propane (74-98-6)		
Vaporizer	Aerosol	
Viscosity, kinematic	0.016 mm ² /s	
Cumene (98-82-8)		
Viscosity, kinematic	0.74 mm²/s Temp.: 'other:37.78°C' Parameter: 'kinematic viscosity (in mm²/s)'	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term

: Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term

(chronic)

: Very toxic to aquatic life with long lasting effects.

Not rapidly degradable

742-48-9)
2200 mg/l Source: IUCLID
2.6 mg/l Source: IUCLID
5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
3.3 mg/l
7.4 mg/l
3.2 – 4.9 mg/l (Selenastrum capricornutum, Growth)
4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
2993 mg/l Test organisms (species): Pimephales promelas
308 mg/l Test organisms (species): Daphnia magna
1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Safety Data Sheet

Methyl ethyl ketone (78-93-3)	
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic algae	93 mg/l
copper (7440-50-8)	
LC50 - Fish [1]	810 µg/l (APHA, 96 h, Cyprinus carpio, Fresh water, Experimental value)
EC50 - Crustacea [1]	792 μg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	3.7 mg/l
EC50 - Crustacea [1]	0.42 mg/l
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic crustacea	0.956 mg/l
toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
EC50 - Crustacea [1]	3.78 mg/l
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
NOEC chronic crustacea	0.74 mg/l
methyl propyl ketone (107-87-9)	
LC50 - Fish [1]	1210 mg/l
EC50 - Crustacea [1]	> 110 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 150 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	> 150 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Methyl isobutyl ketone (108-10-1)	
LC50 - Fish [1]	505 mg/l
LC50 - Fish [2]	> 179 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	1250 mg/l
EC50 96h - Algae [1]	400 mg/l (Selenastrum capricornutum, Literature study, Growth rate)
NOEC chronic fish	57 mg/l
NOEC chronic crustacea	7.8 mg/l
cobalt(II) 2-ethylhexanoate (136-52-7)	
LC50 - Fish [1]	1.512 mg/l (ASTM, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Readacross)

Safety Data Sheet

cobalt(II) 2-ethylhexanoate (136-52-7)	
LC50 - Fish [2]	54.1 mg/l (ASTM, 96 h, Pimephales promelas, Flow-through system, Fresh water, Readacross)
EC50 - Other aquatic organisms [1]	1703 mg/kg dwt (ASTM, 28 day(s), Tubifex tubifex, Semi-static system, Fresh water, Read-across, Reproduction)
ErC50 algae	144 μ g/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
cyclohexane (110-82-7)	
LC50 - Fish [1]	4.53 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.9 mg/l
EC50 72h - Algae [1]	3.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	9.317 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	9.317 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)
NOEC chronic algae	0.94 mg/l
butyl glycolether (111-76-2)	
LC50 - Fish [1]	116 mg/l
EC50 - Crustacea [1]	130 mg/l
EC50 72h - Algae [1]	911 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1840 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'
N-methyl-2-pyrrolidone (872-50-4)	
LC50 - Fish [1]	> 500 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1107 mg/l (EPA 660/3 - 75/009, 96 h, Palaemonetes vulgaris, Static system, Salt water, Experimental value)
EC50 - Crustacea [2]	> 1000 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h - Algae [1]	600.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 500 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	12.5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	12.5 mg/l
Propane (74-98-6)	
LC50 - Fish [1]	24 mg/l (96 h, Pisces, Literature study)
LC50 - Fish [2]	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 - Crustacea [1]	7 mg/l (48 h, Daphnia magna, Literature study)
Cumene (98-82-8)	
LC50 - Fish [1]	2.7 mg/l
LC50 - Fish [2]	4.8 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.2 mg/l
	·

Safety Data Sheet

Cumene (98-82-8)			
EC50 72h - Algae [1]	2.01 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
EC50 72h - Algae [2]	1.29 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
ErC50 algae	2.01 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)		
NOEC (chronic)	0.35 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic fish	0.38 mg/l Test organisms (species): other:D. rerio and P. promelas Duration: '28 d'		
NOEC chronic crustacea	0.35 mg/l		
NOEC chronic algae	0.22 mg/l		
12.2. Persistence and degradability			
acetone (67-64-1)			
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance		
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance		
ThOD	2.2 g O ₂ /g substance		
BOD (% of ThOD)	0.872 (20 day(s), Literature study)		
Xylene (1330-20-7)			
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	1.4 − 2.53 g O ₂ /g substance		
Chemical oxygen demand (COD)	2.56 – 2.91 g O ₂ /g substance		
ThOD	3.1 g O ₂ /g substance		
BOD (% of ThOD)	0.44 – 0.816		
Methyl ethyl ketone (78-93-3)			
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	2.03 g O₂/g substance		
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance		
ThOD	2.44 g O ₂ /g substance		
copper (7440-50-8)			
Persistence and degradability	Biodegradability: not applicable.		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
Ethylbenzene (100-41-4)			
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance		
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance		
ThOD	3.17 g O₂/g substance		
toluene (108-88-3)			
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance		
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance		
ThOD	3.13 g O ₂ /g substance		
BOD (% of ThOD)	0.69		
	I		

Safety Data Sheet

methyl propyl ketone (107-87-9)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Methyl isobutyl ketone (108-10-1)		
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	2.06 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.16 g O ₂ /g substance	
ThOD	2.72 g O ₂ /g substance	
BOD (% of ThOD)	0.76	
cobalt(II) 2-ethylhexanoate (136-52-7)		
Persistence and degradability	Readily biodegradable in water.	
cyclohexane (110-82-7)		
Persistence and degradability	Not degradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.22 g O₂/g substance	
ThOD	3.425 g O ₂ /g substance	
butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water.	
N-methyl-2-pyrrolidone (872-50-4)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.07 g O₂/g substance	
Chemical oxygen demand (COD)	1.56 g O ₂ /g substance	
ThOD	1.9 g O ₂ /g substance	
BOD (% of ThOD)	0.56	
Propane (74-98-6)		
Persistence and degradability	Readily biodegradable in water.	
Cumene (98-82-8)		
Persistence and degradability	Not readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.28 g O₂/g substance	
Chemical oxygen demand (COD)	2.42 g O ₂ /g substance	
ThOD	3.2 g O ₂ /g substance	
12.3. Bioaccumulative potential		
naphtha (petroleum), hydrotreated heavy (
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID	
acetone (67-64-1)		
BCF - Fish [1]	0.69 (Pisces)	
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)	
Bioaccumulative potential	Not bioaccumulative.	
Xylene (1330-20-7)		
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Readacross)	
BCF - Fish [2]	14.1 – 15 (Carassius auratus)	
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)	

Safety Data Sheet

Methyl ethyl ketone (78-93-3)		
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
copper (7440-50-8)		
Bioaccumulative potential	Not bioaccumulative.	
Ethylbenzene (100-41-4)		
BCF - Fish [1]	1 – 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)	
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
toluene (108-88-3)		
BCF - Fish [1]	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
methyl propyl ketone (107-87-9)		
Partition coefficient n-octanol/water (Log Pow)	0.857 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Methyl isobutyl ketone (108-10-1)		
BCF - Fish [1]	2 – 5 (Pisces, Estimated value)	
Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
cobalt(II) 2-ethylhexanoate (136-52-7)		
BCF - Fish [1]	1.2 (131 day(s), Seriola quinqueradiata, Static system, Salt water, Read-across, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	2.96 Source: ECHA	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
cyclohexane (110-82-7)		
BCF - Fish [1]	167 (Pimephales promelas, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	3.44 (Experimental value, Other, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
butyl glycolether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
N-methyl-2-pyrrolidone (872-50-4)		
BCF - Other aquatic organisms [1]	3 (Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-0.46 Source: ECHA	
Bioaccumulative potential	Not bioaccumulative.	
Propane (74-98-6)		
BCF - Fish [1]	9 – 25 (Pisces, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

Safety Data Sheet

Cumene (98-82-8)	
BCF - Other aquatic organisms [1]	94.69 l/kg (BCFBAF v3.00, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	3.55 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
12.4. Mobility in soil	
acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test) data on mobility of the substance available.
Xylene (1330-20-7)	
Mobility in soil	537 Source: ECHA
Surface tension	28.01 – 29.76 mN/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
Methyl ethyl ketone (78-93-3)	
Surface tension	0.024 N/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.53 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.
copper (7440-50-8)	
Ecology - soil	No (test)data on mobility of the components available.
Ethylbenzene (100-41-4)	
Surface tension	0.071 N/m (23 °C, 0.0582 g/l, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.
toluene (108-88-3)	
Surface tension	27.73 N/m (25 °C)
Ecology - soil	Low potential for adsorption in soil.
methyl propyl ketone (107-87-9)	
Surface tension	23.87 mN/m (20 °C, 100 %, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.915 – 1.624 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Methyl isobutyl ketone (108-10-1)	
Mobility in soil	101.85 Source: ECHA
Surface tension	0.024 N/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.008 (log Koc, Weight of evidence, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
cobalt(II) 2-ethylhexanoate (136-52-7)	
Surface tension	0.064 N/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	No (test) data on mobility of the substance available.
<u> </u>	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amende	u by Negulation (LO) 2020/070	
cyclohexane (110-82-7)		
Mobility in soil	770 Source: ECHA	
Surface tension	0.025 N/m (20 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.89 (log Koc, QSAR)	
Ecology - soil	Low potential for adsorption in soil.	
butyl glycolether (111-76-2)		
Surface tension	65.03 mN/m (20 °C, 2 g/l)	
Ecology - soil	Low potential for adsorption in soil.	
N-methyl-2-pyrrolidone (872-50-4)		
Surface tension	0.407 N/m	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)	
Ecology - soil	Highly mobile in soil.	
Propane (74-98-6)		
Surface tension	0.016 N/m (-47 °C)	
Ecology - soil	Not applicable.	
Cumene (98-82-8)		
Surface tension	28.2 mN/m (20 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.946 (log Koc, Calculated value)	
Ecology - soil	Low potential for adsorption in soil.	
12.5. Results of PBT and vPvB assessment		
Component		
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XI	
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Methyl ethyl ketone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XI	
copper (7440-50-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XI	
2-phenoxyethanol (122-99-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XII	

Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Methyl ethyl ketone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
copper (7440-50-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-phenoxyethanol (122-99-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
toluene (108-88-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
methyl propyl ketone (107-87-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Methyl isobutyl ketone (108-10-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
cobalt(II) 2-ethylhexanoate (136-52-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
cyclohexane (110-82-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
butyl glycolether (111-76-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
N-methyl-2-pyrrolidone (872-50-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Component	
Propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Cumene (98-82-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

n accordance with ADR / IIVIL	JG / IA I A / ADIN / RID			
ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
1 1 1 1 1 1 1 1 1 1		1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1	
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes

No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11
Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, : CV9, CV12

unloading and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

07/12/2023 (Revision date) GB - en 26/30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) :

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, : CW9, CW12

unloading and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

07/12/2023 (Revision date) GB - en 27/30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: 1-Methyl-2-pyrrolidone (NMP) (EC 212-828-1, CAS 872-50-4)

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Acetone	67-64-1	2914 11 00	ex 3824 99 92
Name	CAS-No.	Nomenclature	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information		
Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	

Safety Data Sheet

Abbreviations and acronyms:		
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:			
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4		
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aerosol 1	Aerosol, Category 1		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1A	Flammable gases, Category 1A		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H302	Harmful if swallowed.		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.