

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 1/31/2020 Revision date: 10/14/2022 Supersedes: 2/17/2022 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Trade name : MOLY-MIST™ Aerosol

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricant

1.3. Supplier

Distributor

Whitmore Manufacturing LLC 930 Whitmore Drive Rockwall, Texas, 75087 USA

T 1.972.771.1000

Regulatory@whitmores.com - www.jetlube.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week

Within USA and Canada: 1.800.424.9300 Outside USA and Canada: +1.703.527.3887

(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Carcinogenicity Category 2	H351	Suspected of causing cancer
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H222 - Extremely flammable aerosol

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
acetone	CAS-No.: 67-64-1	30 – 36	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl ethyl ketone	CAS-No.: 78-93-3	15 – 19	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Xylene (Note C)	CAS-No.: 1330-20-7	8.172 – 11.704	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H336
methyl propyl ketone	CAS-No.: 107-87-9	4.2 – 4.4	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Ethylbenzene	CAS-No.: 100-41-4	0.168 – 0.176	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

10/14/2022 (Revision date) US - en 2/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Exercise caution. Spill area may be slippery.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

Acetone

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

MOLY-MIST™ Aerosol

No additional information available

acetone (67-64-1)

Local name

USA - ACGIH - Occupational Exposure Limits

HOA COHA Commedianal Francesco Limite	
Regulatory reference	ACGIH 2021
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH OEL STEL [ppm]	500 ppm
ACGIH OEL TWA [ppm]	250 ppm

USA - OSHA - Occupational Exposure Limits

Local name	Acetone
OSHA PEL (TWA) [1]	2400 mg/m³
OSHA PEL (TWA) [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Methyl ethyl ketone (78-93-3)

JSA - ACGIH - Occupational Exposure Limits

USA - ACGIH - Occupational Exposure Limits		
Local name	Methyl ethyl ketone (MEK)	
ACGIH OEL TWA [ppm]	200 ppm	
ACGIH OEL STEL [ppm]	300 ppm	

10/14/2022 (Revision date) US - en 3/16

Safety Data Sheet

Methyl ethyl ketone (78-93-3)		
Remark (ACGIH)	TLV® Basis: URT irr; CNS & PNS impair. Notations: BEI	
Regulatory reference	ACGIH 2021	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butanone (Methyl ethyl ketone)	
OSHA PEL (TWA) [1]	590 mg/m³	
OSHA PEL (TWA) [2]	200 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Xylene (1330-20-7)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Xylene, mixed isomers (Dimethylbenzene)	
ACGIH OEL TWA [ppm]	100 ppm	
ACGIH OEL STEL [ppm]	150 ppm	
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
Regulatory reference	ACGIH 2021	
USA - OSHA - Occupational Exposure Limits		
Local name	Xylenes (o-, m-, p-isomers)	
OSHA PEL (TWA) [1]	435 mg/m³	
OSHA PEL (TWA) [2]	100 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
methyl propyl ketone (107-87-9)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Methyl propyl ketone	
ACGIH OEL STEL [ppm]	150 ppm	
Remark (ACGIH)	TLV® Basis: Pulm func; eye irr	
Regulatory reference	ACGIH 2021	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Pentanone (Methyl propyl ketone)	
OSHA PEL (TWA) [1]	700 mg/m³	
OSHA PEL (TWA) [2]	200 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Ethylbenzene (100-41-4)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethylbenzene	
	Ethylbenzene 20 ppm	
Local name	· ·	
Local name ACGIH OEL TWA [ppm]	20 ppm TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed	
Local name ACGIH OEL TWA [ppm] Remark (ACGIH)	20 ppm TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI	
Local name ACGIH OEL TWA [ppm] Remark (ACGIH) Regulatory reference	20 ppm TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)	
OSHA PEL (TWA) [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Neoprene or nitrile rubber gloves

Туре	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	2 (> 30 minutes)	0.3 mm - 0.6 mm	

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosols.
Color : Black
Odor : Acetone odour

Odor threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available : No data available

Boiling point : > 36 °C (Based on components)

: < 0 °C (Liquid portion) Flash point Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available : Insoluble in water. Solubility Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available

9.2. Other information

Explosive properties

Oxidizing properties

Gas group : Press. Gas (Liq.)

10/14/2022 (Revision date) US - en 5/16

: No data available

: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (ilinalation)	. Not classified
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
Methyl ethyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat (Vapours)	34.5 mg/l/4h
ATE US (oral)	2193 mg/kg body weight
ATE US (vapors)	34.5 mg/l/4h
Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LD50 dermal	1700 mg/kg
LC50 Inhalation - Rat (Vapours)	27.57 mg/l/4h
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1700 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
methyl propyl ketone (107-87-9)	
LD50 oral rat	1600 – 3200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral

Toxicity)

Safety Data Sheet

methyl propyl ketone (107-87-9)		
LC50 Inhalation - Rat	> 25.5 mg/l air Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)	
ATE US (oral)	1600 mg/kg body weight	
Ethylbenzene (100-41-4)		
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)	
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)	
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))	
ATE US (oral)	3500 mg/kg body weight	
ATE US (dermal)	15432 mg/kg body weight	
ATE US (gases)	4500 ppmV/4h	
ATE US (vapors)	17.8 mg/l/4h	
ATE US (dust, mist)	1.5 mg/l/4h	
Skin corrosion/irritation :	Causes skin irritation.	
acetone (67-64-1)		
рН	7 (10 g/l)	
methyl propyl ketone (107-87-9)		
рН	No data available in the literature	
Serious eye damage/irritation :	Causes serious eye irritation.	
acetone (67-64-1)		
рН	7 (10 g/l)	
methyl propyl ketone (107-87-9)		
рН	No data available in the literature	
Respiratory or skin sensitization :	Not classified	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Suspected of causing cancer.	
Xylene (1330-20-7)		
IARC group	3 - Not classifiable	
Ethylbenzene (100-41-4)		
IARC group	2B - Possibly carcinogenic to humans	
Reproductive toxicity : Not classified		
acetone (67-64-1)		
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female	
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)	
STOT-single exposure :	May cause drowsiness or dizziness.	
acetone (67-64-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
Methyl ethyl ketone (78-93-3)		
STOT-single exposure	May cause drowsiness or dizziness.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

May cause drowsiness or dizziness. : Not classified 150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408		
: Not classified 150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408		
150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408		
(Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)		
Ethylbenzene (100-41-4)		
75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)		
May cause damage to organs through prolonged or repeated exposure.		
: Not classified		
: No data available		
acetone (67-64-1)		
0.417 mm²/s		
Methyl ethyl ketone (78-93-3)		
0.494 mm²/s		
0.74 mm²/s (20 °C)		
methyl propyl ketone (107-87-9)		
No data available in the literature		
Ethylbenzene (100-41-4)		
0.773 mm²/s (20 °C, OECD 114: Viscosity of Liquids)		

SECTION 12: Ecological information

12.	1.	Toxicity

: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Ecology - general

acetone (67-64-1)		
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)	
EC50 96h - Algae [1]	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
Methyl ethyl ketone (78-93-3)		
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas	
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
NOEC chronic algae	93 mg/l	

10/14/2022 (Revision date) US - en 8/16

Safety Data Sheet

Xylene (1330-20-7)		
LC50 - Fish [1]	3.3 mg/l	
EC50 - Crustacea [1]	7.4 mg/l	
EC50 72h - Algae [1]	3.2 – 4.9 mg/l (Selenastrum capricornutum, Growth)	
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'	
methyl propyl ketone (107-87-9)		
LC50 - Fish [1]	1210 mg/l	
EC50 - Crustacea [1]	> 110 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 150 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
ErC50 algae	> 150 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
Ethylbenzene (100-41-4)		
LC50 - Fish [1]	3.7 mg/l	
EC50 - Crustacea [1]	0.42 mg/l	
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum	
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum	
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC chronic crustacea	0.956 mg/l	
12.2. Persistence and degradability		
acetone (67-64-1)		
Not rapidly degradable		
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance	
ThOD	2.2 g O ₂ /g substance	
BOD (% of ThOD)	0.872 (20 day(s), Literature study)	
Methyl ethyl ketone (78-93-3)		
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	2.03 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance	
ThOD	2.44 g O ₂ /g substance	
Xylene (1330-20-7)		
Not rapidly degradable		

Safety Data Sheet

Xylene (1330-20-7)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.4 – 2.53 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.56 – 2.91 g O ₂ /g substance	
ThOD	3.1 g O ₂ /g substance	
BOD (% of ThOD)	0.44 – 0.816	
methyl propyl ketone (107-87-9)		
Not rapidly degradable		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Ethylbenzene (100-41-4)		
Not rapidly degradable		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.44 g O₂/g substance	
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance	
ThOD	3.17 g O ₂ /g substance	
12.3. Bioaccumulative potential	3 - 2 3	
acetone (67-64-1)		
BCF - Fish [1]	0.69 (Pisces)	
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)	
Bioaccumulative potential	Not bioaccumulative.	
Methyl ethyl ketone (78-93-3)		
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Xylene (1330-20-7)		
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)	
BCF - Fish [2]	14.1 – 15 (Carassius auratus)	
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
methyl propyl ketone (107-87-9)		
Partition coefficient n-octanol/water (Log Pow)	0.857 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Ethylbenzene (100-41-4)		
BCF - Fish [1]	1 – 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)	
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
12.4. Mobility in soil	·	
acetone (67-64-1)		
Surface tension	0.0237 N/m	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone (67-64-1)		
Ecology - soil	No (test)data on mobility of the substance available.	
Methyl ethyl ketone (78-93-3)		
Surface tension	0.024 N/m (20 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.53 (log Koc, Calculated value)	
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.	
Xylene (1330-20-7)		
Mobility in soil	537 Source: ECHA	
Surface tension	28.01 – 29.76 mN/m (25 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)	
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.	
methyl propyl ketone (107-87-9)		
Surface tension	23.87 mN/m (20 °C, 100 %, EU Method A.5: Surface tension)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.915 – 1.624 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	
Ethylbenzene (100-41-4)		
Surface tension	0.071 N/m (23 °C, 0.0582 g/l, EU Method A.5: Surface tension)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)	
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
1950	UN1950	1950	1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description			
UN1950 Aerosols, 2.1	UN1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
PARMANE GAS	2	2	2
14.4. Packing group		<u> </u>	
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			ı

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1950

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General

Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges

have a capacity less than or equal to 50 mL.

(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L Excepted quantities (TDG) : E0 Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 126

IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None

10/14/2022 (Revision date) US - en 12/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provision (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Xylene CAS-No. 1330-20-7 8.172 – 11.704%

acetone (67-64-1)

CERCLA RQ 5000 lb

Methyl ethyl ketone (78-93-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

Xylene (1330-20-7)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 100 lb

Ethylbenzene (100-41-4)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 1000 lb

15.2. International regulations

CANADA

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

Methyl ethyl ketone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

methyl propyl ketone (107-87-9)

Listed on the Canadian DSL (Domestic Substances List)

Ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

acetone (67-64-1)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Methyl ethyl ketone (78-93-3)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Xylene (1330-20-7)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

methyl propyl ketone (107-87-9)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

MARNING:

This product can expose you to Methyl isobutyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
acetone(67-64-1)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
Methyl ethyl ketone(78-93-3)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
Xylene(1330-20-7)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
molybdenium(IV) sulfide(1317-33-5)	U.S New York City - Right to Know Hazardous Substances List
Petroleum gases,liquefied(68476-85-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
methyl propyl ketone(107-87-9)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
Methyl isobutyl ketone(108-10-1)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
Ethylbenzene(100-41-4)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 10/14/2022

Full text of H-phrases	
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), USA

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.