

DESCRIPTION

Clear liquid spray used to accelerate the cure rate of some Deacon thermosetting compounds. Not recommended above 600°F (316°C).

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

INSTRUCTIONS

After a Deacon sealant is applied to a flange, gasket, or thread, mist Deacon 103-L onto the sealant, assemble the joint, and begin heat exposure. Normal startup procedures can be followed or heat can be applied externally following the recommended cure times:

250°F	2-3 hours
400°F	30-60 minutes

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@deaconindustries.com or write to the Sales Department at the address below.

NOTE

Deacon 103-L will accelerate the curing process, but must be used in conjunction with heat (minimum of 150°F/65°C). Deacon 103-L will not cure the sealant material without heat also being present.

Also available in powder form (Deacon 103-P).

SHELF LIFE

Two years in closed containers.

PACKAGED

2 oz. spray bottle.