

DESCRIPTION

Black, Fibrous, Packing / Sealant, Solid content 100% Natural Graphite.

TEMPERATURE RANGE

-30°F to +1200°F.

APPLICATIONS

Valves. Reduce or eliminate Fugitive Emissions in VOC Valve Packings. Can be hand packed or injected.

CHARACTERISTICS

This is a non-curing, highly compressible compound that is durable and will remain semi-flexible at extreme temperatures and pressures. It is a highly lubricous, low friction, valve packing.

CHEMICAL COMPATIBILITY

This compound is non-reactive to most volatile organic compounds.

SHELF LIFE

2 years in closed containers.

PACKAGED

Quarts, J-Sticks, and 5/8" x 3" plugs.
Other sizes available upon request.

DIRECTIONS

Please be advised that we recommend a top and bottom ring of braided packing still be installed for containment, especially when tolerances are in question.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@jetlube.com