

DESCRIPTION

100% PTFE (fibers, fillers and particles) blended with a food grade lubricant.

TEMPERATURE RANGE

-50°F to 450°F.

APPLICATIONS

Packing and sealant for valves.
Can be hand packed or injected.

CHEMICAL RESISTANCE

Excellent, Inert to most solvents and acids. (NOT) recommended for oxygen service.

NOTE

All ingredients included in Deacon 360-FG are purchased with certification, that they meet either one or more of the following U.S. Food and Drug Administration specifications: 21 CFR 177.1550
21 CFR 178.3620

SHELF LIFE

2 years in closed metal containers.

PACKAGED

Quarts and Gallons.

DIRECTIONS

Please be advised that we recommend an application compatible top and bottom containment ring (braided packing) still be installed, especially when tolerances are in question.

NOTE

Deacon 360-FG has not been tested and approved as a food grade sealant as a whole. We certify that all ingredients included in Deacon 360-FG are certified food grade, and all precautions are taken in mixing and packaging to insure product integrity.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.
CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@jetlube.com