

## DESCRIPTION

White, fibrous, packing/sealant, PTFE mixture with a synthetic carrier.

## TEMPERATURE RANGE

-50°F to 400°F

## APPLICATIONS

Valves sealant/packing.  
Can be hand packed or injected.

## CHARACTERISTICS

This is a non-curing compound with a good lubricity and low friction characteristics.

## CHEMICAL COMPATIBILITY

Excellent, Inert to most solvents, acids, chemicals. For use on Liquid Chlorine service.

## SHELF LIFE

Two years in closed containers.

## PACKAGED

½ pint.  
Other sizes are available upon request.

## DIRECTIONS

Please be advised that we recommend a top and bottom ring of braided packing still be installed for containment, especially when tolerances are in question.

### FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

## LIMITED WARRANTY

For warranty information please visit [http://www.jetlube.com/pdf/Limited\\_Warranty\\_At\\_Delivery\\_Deacon.pdf](http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf) You can also email us at [sales@deaconindustries.com](mailto:sales@deaconindustries.com) or write to the Sales Department at the address below.