

DESCRIPTION

Thread Sealant/Gasket Sealant Paste

TEMPERATURE RANGE

-25°F to 450°F

APPLICATIONS

For use on Threaded Connection, Flanges, Cover Plates, Valve Cover Gaskets, and any Metal to Metal Joints.

CHEMICAL COMPATIBILITY

Excellent Resistance to Oils, Water, Steam, Di-Ester Type Fluids, Diesel Fuels, Gasoline, Greases, Ethylene Glycol, Transmission Fluid, and Aliphatic Hydrocarbons.

FEATURES

Viscous Paste, Slow Drying, Remains Pliable, Improves Reliability, Extends Gasket Life, Stops Leakage, Will Not Interfere with Future Repairs or Maintenance.

SHELF LIFE

Two years in closed containers

PACKAGED

10.3 fl. Oz. Caulking Tube, Pint Brush Top, Quart

DIRECTIONS

Please be advised that we recommend a top and bottom ring of braided packing still be installed for containment, especially when tolerances are in question.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@deaconindustries.com or write to the Sales Department at the address below.