



## BOOSTER KIT

---

### PRODUCT DESCRIPTION:

BOOSTER KIT is designed for building large transitions over flanges, or leak sealing clamps prior to installing the ROCKET WRAP composite repair system. Each kit includes a two-part epoxy (resin and hardener) and aggregate.

### FEATURES:

- Min/Max Service temperatures: -50°F to 350°F (-46°C to 177°C)
- Application temperatures: 50°F to 120°F (10°C to 49°C)
- Pot life (77°F / 25°C): 30-50 minutes
- Tack free time (77°F / 25°C): 4 hours.
- Thick and will not sag when applied in vertical overhead applications.
- Booster powder (aggregate) creates superior strength and volumetric expansion.

### INSTRUCTIONS FOR USE:

1. Combine the entire contents of Part A and Part B into the provided bucket.
2. Mix for 3 minutes with a drill type paddle mixer (until uniform color and consistency is achieved).
3. Scrape the sides to ensure there are no unmixed A/B materials.
4. Add 1/2 of one bag of booster powder and mix until smooth.
5. Repeat until all booster powder is added and consistently mixed.
6. Apply using a trowel, spatula, or by hand to create the desired shape.

### STORAGE AND HANDLING:

Shelf life of the BOOSTER KIT is 24 months at 77°F (25°C). For best results, store in original, tightly closed containers in a cool, dry place out of direct sunlight.

### PACKAGING:

Small Kit (400 Gram Kit Rocket Saturant, Booster Powder, Accessories)

Large Kit (800 Gram Kit Rocket Saturant, Booster Powder, Accessories)

### LIMITED WARRANTY

For warranty information please visit

[http://www.jetlube.com/pdf/Limited\\_Warranty\\_At\\_Delivery\\_Deacon.pdf](http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf) You can also email us at [sales@jetlube.com](mailto:sales@jetlube.com)