

TYPICAL APPLICATIONS

Rotary Pumps, Valves, Centrifugal Pumps, Agitators, Reciprocating Pumps, Mixers, Turbine Pumps, Refiners, Dryers, Non-Staining.

TEMPERATURE RANGE

-50°F to +450°F.

PRESSURE

0 to 300 PSI

SHAFT SPEED

4150 SFM

pH

0 – 14

PACKAGING

1lb. (approx. 14 cu. In.)

FEATURES

Putty-like form eliminates the need to stock by size. Minimal downtime- repack simply by adding additional Pump 77 as needed (old Pump 77 does not need to be removed). High temperature and pressure ranges. Permanently pliable, 100% consumable, high chemical resistance,

DIRECTIONS

Please be advised that we recommend a top and bottom ring of braided packing still be installed for containment, especially when tolerances are in question.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

LIMITED WARRANTY

For warranty information please visit You can also email us at sales@deaconindustries.com or write to the Sales Department at the address below.