

## VP-1000

## VP-1200

NON CURING  
SEALANT / PACKING

**Description:** Injectable Valve Packing and sealant containing assorted fibers, fillers, dry lubricants, suspended in a synthetic carrier base.

**Temperature Range:**

VP-1000: -25°F. (-31°C.) to 600°F. (315°C.)

VP-1200: up to 1200°F (649°C)

**Characteristics:** (non-curing compound)

Excellent travel, good lubricity, good on water, steam, and air leaks.

**Applications:** Valve packing and sealant for valves and enclosures.

**Shelf Life:** One year minimum in closed container.

**Packaged:** 5/8 x 3 Plugs, J-Sticks, Gallons.

**Procedure Warning:** (For industrial use by professionally trained personnel only) If being injected, steps should be taken to insure that the injection pressure in conjunction with pressure that may occur from gassing off of the compound does not exceed the pressure limitations of the piping system. If the compound is gassing off, gasses should be vented. Also, be aware it is quite common that the application temperature will exceed the compound flash point. Be aware of the possibility of a flash and take necessary precautions. See section 8 of SDS for personal protective equipment. Refer to product SDS and technical data for reactivity and compatibility information.

**FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.**

CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE.

**NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

Disclaimer: The information & recommendations of Jet-Lube LLC / Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Jet-Lube LLC / Deacon, the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Jet-Lube LLC / Deacon recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.

[info@deacon-intlsales.com](mailto:info@deacon-intlsales.com) (800) 552-2896 or (724) 225-8008