



# CLEAN-UP™ AEROSOL

## INDUSTRIAL GRADE DEGREASER & SAFETY SOLVENT

### DESCRIPTION

**CLEAN-UP™** is an industrial strength, specially formulated blend of non-flammable solvents. Not for use in California. See SDS for additional OTC/LADCO state restrictions. In California and other CARB states use CLEAN UP II.

**CLEAN-UP™** should be used to dissolve grease, oil, wax, paint, grime, dirt, and dust.

**CLEAN-UP™** does not contain acids or alkalis and will not damage metal surfaces. Do not use on surfaces affected by petroleum solvents such as rubber, paint, some plastics, and synthetic fabrics. Not to be used on sensitive electronic equipment.

**Use in well ventilated areas only.**

- NSF Registered K1 Reg# 137558
- Nonflammable
- Penetrates Quickly
- Ozone Friendly
- Acid, Alkali Free
- Low Odor
- 53 kv Dielectric Strength

### APPLICATIONS

**CLEAN-UP** is ideal for cleaning items such as:

Engine Components	Bearings
Motors	Appliances
Machine Parts	Cables
Chrome	Tools
Gears	Metal Surfaces
Chains	Injectors

Not for use in California.  
See SDS for additional OTC/LADCO state restrictions.

**VOC content exempt per 40 CFR EXEMPT – EPA 61 FR 4588**

### PRODUCT CHARACTERISTICS

Spray Pattern—Typical	Tight Stream
Propellant	Carbon Dioxide
Solvent Type	Chlorinated
Specific Gravity	1.5
Density (lb/gal)	12.2
Flash Point	None
Dielectric Strength	
(ASTM D-877)	>53 KV
Flame Extension	No Flame
NFPA 30B Storage Class	Level 1
VOC Content	Exempt

### LIMITED WARRANTY

For warranty information please visit

[http://www.jetlube.com/pdf/Jet-Lube\\_Warranty.pdf](http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf)

You can also email us at [sales@jetlube.com](mailto:sales@jetlube.com) or write to the Sales Department at the address below.