



EZY-TURN® #2 PLUS

FRAC VALVE LUBRICANT

DESCRIPTION

EZY-TURN® #2 Plus is a Frac Valve Lubricant for use where hydrocarbon resistance is important.

EZY-TURN® #2 Plus is formulated from a blend of synthetic oils that are chemically stable and naturally corrosion resistant which provides excellent pumpability in cold weather. Added to this blend are hydrogen sulfide (H₂S) and rust inhibitors. The product contains no solid fillers. This formulation produces a clear amber lubricant with excellent sealing properties.

EZY-TURN® #2 Plus will lubricate and protect precision gate valves from scoring, galling, and corrosion. It is easily pumped with a high-pressure lubricator at temperatures as low as -20 °F (-29°C). This formulation is extremely resistant to water and hydrocarbons making it the product of choice for general industrial and oilfield use.

- Chemically Stable
- Injectable
- Hydrocarbon Resistant
- Nontoxic
- H₂S Inhibited
- Corrosion Resistant
- Biodegradable
- Water Resistant
- Pumpable in cold weather
- No Solid Fillers

APPLICATIONS

EZY-TURN® #2 Plus is recommended for use in a wide variety of production applications and services such as crude, salt water, gas, dilute acid and other mixtures are encountered.

SERVICE RATING

-20 °F (-29°C) to 450°F (232°C)

Note: Not for use with oxygen for strong oxidizers such as hydrogen peroxide or sulfuric acid.

PRODUCT CHARACTERISTICS

Appearance	Paste
Color	Gold to Amber
Thickener	Inorganic
Cone Penetration, mm x 10 ⁻¹ (ASTM D-217)	220 – 250
Density (lb/gal)	8.60 Typical
Specific Gravity	1.03
Dropping Point (ASTM D-2265)	None
Oil Separation, Wt % (ASTM D-6184)	5.0 Maximum

For package types and part numbers

www.jetlube.com/resources/product-index/

Limited Warranty

www.jetlube.com/assets/documents/Jet-Lube_Warranty.pdf