



WHITE LITHIUM GREASE AEROSOL WITH PTFE

DESCRIPTION

WHITE LITHIUM GREASE with PTFE is a premium, all-purpose grease in a convenient aerosol spray package that provides superior performance and protection for metal and moving parts under any use.

WHITE LITHIUM GREASE with PTFE AEROSOL penetrates and forms a long-lasting protective film to withstand heavy loads and high speeds, prevents rust and corrosion, eliminates squeaks and squeals and will not run or wash away.

WHITE LITHIUM GREASE with PTFE is excellent for all metal-to-metal lubrication and is the preferred lubricant for use in the plant, shop, home, auto and boat.

- Convenient aerosol package
- NSF Reg. #137550
- Clean, White Color
- Multi-Purpose
- Water Resistant
- Prevent Rust and Corrosion
- Very Adhesive
- Resists Heat and Oxidation

APPLICATIONS

GENERAL PURPOSE LUBRICANT

INDUSTRIAL - machinery, tools, overhead garage door channels, fan motors, slides, gears...

MARINE - cables, couplings, gears, hitches, winches...

AUTOMOTIVE - hinges, electric antennas, latches, springs, coils...

RESIDENTIAL - implements, door channels, slides, locks...

FOOD SERVICE - all areas where food contact cannot occur.

SERVICE RATING:
0°F (-18°C) to 370°F (190°C)

- **NSF (H-2) Registered, Meets 1998 USDA (H-2) Guidelines For Use In Federally Inspected Meat and Poultry Plants in Noncontact Areas**
- **Authorized for use by Agriculture Canada**

PRODUCT CHARACTERISTICS

Propellant	Hydrocarbon
Spray Pattern	2" - 4" Cone
VOC Content	422g/Liter (Includes Propellant)
NFPA 30B Storage Class	Level III
Thickener	Lith. 12-hydroxy
Fluid Type	Petroleum Oil
Color/Appearance	White
Dropping Point (ASTM D-566)	390°F (199°C)
Specific Gravity	0.72 (Includes Propellant)
Additive Type	Organic E/P, A/W, R&O
Flash Point (ASTM D-92)	<64°F (<18°C)
Autoignition Point (calculated)	>500°F (260°C)
Penetration @ 77°F (ASTM D-217)	265 – 295
Copper Strip Corrosion (ASTM D-4048)	1A
Shell 4-Ball (ASTM D-2596)	
Weld Point, kgf	200
Load Wear Index	25
Wear Scar Diameter (ASTM D-2266)	0.7

For package types and part numbers contact sales@jetlube.com.

LIMITED WARRANTY

For warranty information please visit

http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.